

TP-LINK Powerline sada AV600 + WiFi extender 300Mbps/2.4GHz, HomePlug AV 600Mbps

cena vč DPH: **1613 Kč**

cena bez DPH: 1332.67 Kč

Kód zboží (ID): 1429169

PN: TL-WPA4220KIT

Záruka: 36 měsíců

Startovací sada AV600 Wi-Fi Powerline Extender s rychlostí 300 Mb/s TL-WPA4220KIT Tlačítko klonování Wi-Fi pro velké rozšíření dosahu zjednodušuje konfiguraci Wi-Fi a pomáhá vytvořit jednotnou bezproblémovou domácí síť Standard HomePlug AV nabízí prostřednictvím domácí elektrické sítě vysokorychlostní přenos dat rychlostí až 600 Mbit/s, která je ideální pro streamování HD nebo 3D videa a hraní online her Rozšiřte 300Mbit/s bezdrátové připojení do dříve těžko přístupných míst vašeho domova a kanceláře

HARDWARE FEATURES Plug Type EU, UK, US, AR Standards and Protocols HomePlug AV, IEEE802.3, IEEE802.3u, IEEE802.11b/g/n Interface 2*10/100Mbps Ethernet Port Button Pair, Reset, Wi-Fi/Wi-Fi Clone Power Consumption Maximum: 7.608W (220V/50Hz) Typical: 7.216W (220V/50Hz) Standby: 4.610W (220V/50Hz) LED Indicator PWR, PLC, ETH, Wi-Fi/Wi-Fi Clone Dimensions (W x D x H) TL-WPA4220: 2.1 x 1.6 x 3.7 in. (54 x 40 x 94 mm) TL-PA4010: 2.0 x 1.1 x 2.6 in. (52 x 28.5 x 65 mm) Range 300 Meters over electrical circuit

WIRELESS FEATURES Frequency 2.4-2.4835GHz Signal Rate 11n: Up to 300Mbps(dynamic) 11g: Up to 54Mbps(dynamic) 11b: Up to 11Mbps(dynamic) Reception Sensitivity 270M: -68dBm@10% PER 130M: -68dBm@10% PER 108M: -68dBm@10% PER 54M: -68dBm@10% PER 11M: -85dBm@8% PER 6M: -88dBm@10% PER 1M: -90dBm@8% PER Wireless Security 64/128-bit WEP / WPA / WPA2,WPA-PSK / WPA2-PSK Advanced Functions Enable/DisableWireless Radio,WMM, Wireless Statistics Transmission Power CE:<20dBm(2.4GHz) FCC:<30dBm

SOFTWARE FEATURES Modulation Technology OFDM (PLC) Encryption Powerline Security: 128-bit AES Wireless Security: WEP, WPA/WPA2, WPA-PSK/WPA2-PSK Encryption

Startovací sada AV600 Wi-Fi Powerline Extender s rychlostí 300 Mb/s TL-WPA4220KIT Tlačítko klonování Wi-Fi pro velké rozšíření dosahu zjednodušuje konfiguraci Wi-Fi a pomáhá vytvořit jednotnou bezproblémovou domácí síť Standard HomePlug AV nabízí prostřednictvím domácí elektrické sítě vysokorychlostní přenos dat rychlostí až 600 Mbit/s, která je ideální pro streamování HD nebo 3D videa a hraní online her Rozšiřte 300Mbit/s bezdrátové připojení do dříve těžko přístupných míst vašeho domova a kanceláře

HARDWARE FEATURES Plug Type EU, UK, US, AR Standards and Protocols HomePlug AV, IEEE802.3, IEEE802.3u, IEEE802.11b/g/n Interface 2*10/100Mbps Ethernet Port Button Pair, Reset, Wi-Fi/Wi-Fi Clone Power Consumption Maximum: 7.608W (220V/50Hz) Typical: 7.216W (220V/50Hz) Standby: 4.610W (220V/50Hz) LED Indicator PWR, PLC, ETH, Wi-Fi/Wi-Fi Clone Dimensions (W x D x H) TL-WPA4220: 2.1 x 1.6 x 3.7 in. (54 x 40 x 94 mm) TL-PA4010: 2.0 x 1.1 x 2.6 in. (52 x 28.5 x 65 mm) Range 300 Meters over electrical circuit WIRELESS FEATURES Frequency 2.4-2.4835GHz Signal Rate 11n: Up to 300Mbps(dynamic) 11g: Up to 54Mbps(dynamic) 11b: Up to 11Mbps(dynamic) Reception Sensitivity 270M: -68dBm@10% PER 130M: -68dBm@10% PER 108M: -68dBm@10% PER 54M: -68dBm@10% PER 11M: -85dBm@8% PER 6M: -88dBm@10% PER 1M: -90dBm@8% PER Wireless Security 64/128-bit WEP / WPA / WPA2,WPA-PSK / WPA2-PSK Advanced Functions Enable/Disable Wireless Radio,WMM, Wireless Statistics Transmission Power CE:<20dBm(2.4GHz) FCC:<30dBm

SOFTWARE FEATURES Modulation Technology OFDM (PLC) Encryption Powerline Security: 128-bit AES Wireless Security: WEP, WPA/WPA2, WPA-PSK/WPA2-PSK Encryption