TP-Link TL-SF1008D Switch 8xTP 10/100Mbps

cena vč DPH:	**362 Kč**
cena bez DPH:	299.18 Kč

Kód zboží (ID):	21354
PN:	TL-SF1008D
Záruka:	36 měsíců

8portový stolní switch 10/100 Mbit/s TL-SF1008D 8 portů 10/100 Mbit/s RJ45 s podporou automatického vyjednávání a Auto MDI/MDIX Ekologická technologie Ethernet přinášející úsporu energie až 70 % Řízení toku IEEE 802.3x zajišťuje spolehlivý přenos dat Plastový obal, stolní design Zapojení typu Plug and Play bez nutnosti konfigurace HARDWARE FEATURES Standards and Protocols IEEE 802.3, IEEE 802.3u, IEEE 802.3x CSMA/CD Interface 8 10/100Mbps Ports, Auto-Negotiation, Auto-MDI/MDIX Fan Quantity Fanless Power Supply External Power Adapter(Output: 9.0VDC / 0.6A) Power Consumption Maximum: 2.2W (220V/50Hz) External Power Supply 100-240VAC, 50/60Hz Buffer Size 2Mb Data Rates 10/100Mbps at Half Duplex ; 20/200Mbps at Full Duplex LED Indicator Power, 1, 2, 3, 4, 5, 6, 7, 8 Dimensions (W x D x H) 5.3*3.1*0.9 in. (134.5*79*22.5mm) SOFTWARE FEATURES Transfer Method Store and Forward Advanced Functions Green Technology, saving power up to 60% 802.3X Flow Control, Back Pressure OTHERS Certification FCC, CE, RoHS Package Contents 8-Port 10/100Mbps Desktop Switch Power Adapter User Guide System Requirements Microsoft® Windows®, XP, Vista or Windows 7, Windows 8, Mac® OS, NetWare®, UNIX® or Linux. Environment Operating Temperature: 0°C~40°C (32°F~104°F); Storage Temperature: -40°C~70°C (-40°F~158°F); Operating Humidity: 10%~90% non-condensing; Storage Humidity: 5%~90% non-condensing

8portový stolní switch 10/100 Mbit/s TL-SF1008D 8 portů 10/100 Mbit/s RJ45 s podporou automatického vyjednávání a Auto MDI/MDIX Ekologická technologie Ethernet přinášející úsporu energie až 70 % Řízení toku IEEE 802.3x zajišťuje

spolehlivý přenos dat Plastový obal, stolní design Zapojení typu Plug and Play bez nutnosti konfigurace HARDWARE FEATURES Standards and Protocols IEEE 802.3, IEEE 802.3u, IEEE 802.3x CSMA/CD Interface 8 10/100Mbps Ports, Auto-Negotiation, Auto-MDI/MDIX Fan Quantity Fanless Power Supply External Power Adapter(Output: 9.0VDC / 0.6A) Power Consumption Maximum: 2.2W (220V/50Hz) External Power Supply 100-240VAC, 50/60Hz Buffer Size 2Mb Data Rates 10/100Mbps at Half Duplex ; 20/200Mbps at Full Duplex LED Indicator Power, 1, 2, 3, 4, 5, 6, 7, 8 Dimensions (W x D x H) 5.3*3.1*0.9 in. (134.5*79*22.5mm) SOFTWARE FEATURES Transfer Method Store and Forward Advanced Functions Green Technology, saving power up to 60% 802.3X Flow Control, Back Pressure OTHERS Certification FCC, CE, RoHS Package Contents 8-Port 10/100Mbps Desktop Switch Power Adapter User Guide System Requirements Microsoft® Windows®, XP, Vista or Windows 7, Windows 8, Mac® OS, NetWare®, UNIX® or Linux. Environment Operating Temperature: 0°C~40°C (32°F~104°F); Storage Temperature: -40°C~70°C (-40°F~158°F); Operating Humidity: 10%~90% non-condensing; Storage Humidity: 5%~90% non-condensing