

Zalman zdroj ZM750-ARX / 750W / ATX / akt. PFC / 135mm ventilátor / 100 - 240V / 80+ Platinum / modular

cena vč DPH: **4511 Kč**

cena bez DPH: 3728 Kč

Kód zboží (ID): 2714204

PN: ZM750-ARX

Záruka: 60 měsíců



Zalman Zdroj ZM750-ARX 750W 80+ Platinum, aPFC, 13,5cm fan, modular AC Input Range: Voltage 100-240VAC \pm 10% Frequency 50Hz ~ 60Hz \pm 3 AC Input Current: 100VAC 10-5A 240VAC 10-5A PFC Type Active PFC Power Factor Correction Max 99% Inrush Current Limit (@ Cold Start at 25C): 100VAC Max 50A 240VAC Max 50A Efficiency Max 94% @ 230VAC, Typical load DC Output Voltage Regulation (At Full Load): Vout Regulation Range +3.3VDC \pm 5% +3.14 ~ +3.47V +5VDC \pm 5% +4.75 ~ +5.25V +12VDC \pm 5% +11.4 ~ 12.6V -12VDC \pm 10% -10.8 ~ -13.0V +5VSB \pm 5% +4.75 ~ +5.25V DC Output Ripple & Noise (At Full Load): Vout Standard Range +3.3VDC 50mV +5VDC 50mV +12VDC 120mV -12VDC 120mV +5VSB 50mV Vout Output Load Rating Combined Power I min I max I peak +3.3V 0.1A 25A 120W 750W +5V 0.2A 22A 120W 750W +12V 0.2A 62A 744W 750W -12V 0.0A 0.3A 3.6W 750W +5VSB 0.0A 2.5A 12.5W 750W Ambient Temperature: Operation 0 ~ 40°C Storage -20 ~ 70°C Ambient Humidity: Operation 5% ~ 95% RH Storage 5% ~ 95% RH Dimensions 180(D) x 150(W) x 86(H)mm Weight 2.9Kg Protection Functions: Over-Current Protection(OCP) Over-Voltage Protection(OVP) Under-Voltage Protection(UVP) Short-Circuit Protection(SCP) Over-Power Protection(OPP) Over-Temperature Protection(OTP) Connectors: MB (20+4Pin) 1x ATX12V (4+4Pin) 1x EPS12V (8Pin) 1x PEI-Ex (6+2Pin) 4x SATA (5pin) 12x Periphial (4pin) 6x FDD (4pin) 1x

Zalman Zdroj ZM750-ARX 750W 80+ Platinum, aPFC, 13,5cm fan, modular AC

Input Range: Voltage 100-240VAC±10% Frequency 50Hz ~ 60Hz±3 AC Input Current: 100VAC 10-5A 240VAC 10-5A PFC Type Active PFC Power Factor Correction Max 99% Inrush Current Limit (@ Cold Start at 25C): 100VAC Max 50A 240VAC Max 50A Efficiency Max 94% @ 230VAC, Typical load DC Output Voltage Regulation (At Full Load): Vout Regulation Range +3.3VDC ±5% +3.14 ~ +3.47V +5VDC ±5% +4.75 ~ +5.25V +12VDC ±5% +11.4 ~ 12.6V -12VDC ±10% -10.8 ~ -13.0V +5VSB ±5% +4.75 ~ +5.25V DC Output Ripple & Noise (At Full Load): Vout Standard Range +3.3VDC 50mV +5VDC 50mV +12VDC 120mV -12VDC 120mV +5VSB 50mV Vout Output Load Rating Combined Power I min I max I peak +3.3V 0.1A 25A 120W 750W +5V 0.2A 22A 120W 750W +12V 0.2A 62A 744W 750W -12V 0.0A 0.3A 3.6W 750W +5VSB 0.0A 2.5A 12.5W 750W Ambient Temperature: Operation 0 ~ 40°C Storage -20 ~ 70°C Ambient Humidity: Operation 5% ~ 95% RH Storage 5% ~ 95% RH Dimensions 180(D) x 150(W) x 86(H)mm Weight 2.9Kg Protection Functions: Over-Current Protection(OCP) Over-Voltage Protection(OVP) Under-Voltage Protection(UVP) Short-Circuit Protection(SCP) Over-Power Protection(OPP) Over-Temperature Protection(OTP) Connectors: MB (20+4Pin) 1x ATX12V (4+4Pin) 1x EPS12V (8Pin) 1x PEI-Ex (6+2Pin) 4x SATA (5pin) 12x Periphal (4pin) 6x FDD (4pin) 1x