

ARCTIC P12

cena vč DPH: **174 Kč**

cena bez DPH: 144 Kč

Kód zboží (ID): 3797562

PN: ACFAN00118A

Záruka: 72 měsíců



Arctic P12, 120x120x25 mm, černý, 3-pin Nová generace ARCTIC větráčků s optimalizovaných pro maximální statický tlak. ARTIC P12 je větráček o rozměru 120x120x25mm, s 1 800 otáčkami při 12V a vzduchovým tranferem: 56.3 CFM (95.65 m3/h), Hlučnost: 0.3 Sone (@ 1 800 RPM) Optimised for Static Pressure - During the development of the new P12, special emphasis was placed on a focused airstream and thus a high static pressure. The fan guarantees extremely efficient cooling, even with increased air resistance. Therefore, the P12 is particularly suitable for use on heatsinks and radiators. High Quality Bearing - Thanks to an alloy/lubricant combination developed in Germany, friction within the bearing is reduced and greater efficiency is achieved. As a result, there is less heat development as well as less bearing noise, which means you can enjoy a longer service life from your fan. Performance Fan: 120 mm, 1 800 RPM (@12 V DC) Air Flow: 56.3 CFM (95.65 m3/h) Noise Level: 0.3 Sone (@ 1 800 RPM) Electrical Characteristics Typical Voltage: + 12 V DC Start-up Voltage: 2.8 V DC Cable Length: 400 mm Voltage Current 12 V DC (Norminal) 0.20 A 7 V DC 0.08 A 5V DC 0.06 A Connection Motherboard: + 12 V DC 3-pin Connector

Arctic P12, 120x120x25 mm, černý, 3-pin Nová generace ARCTIC větráčků s optimalizovaných pro maximální statický tlak. ARTIC P12 je větráček o rozměru 120x120x25mm, s 1 800 otáčkami při 12V a vzduchovým tranferem: 56.3 CFM (95.65 m3/h), Hlučnost: 0.3 Sone (@ 1 800 RPM) Optimised for Static Pressure - During the development of the new P12, special emphasis was placed on a focused airstream and thus a high static pressure. The fan guarantees extremely efficient cooling, even with increased air resistance. Therefore, the P12 is particularly

suitable for use on heatsinks and radiators. High Quality Bearing - Thanks to an alloy/lubricant combination developed in Germany, friction within the bearing is reduced and greater efficiency is achieved. As a result, there is less heat development as well as less bearing noise, which means you can enjoy a longer service life from your fan. Performance Fan: 120 mm, 1 800 RPM (@12 V DC) Air Flow: 56.3 CFM (95.65 m³/h) Noise Level: 0.3 Sone (@ 1 800 RPM) Electrical Characteristics Typical Voltage: + 12 V DC Start-up Voltage: 2.8 V DC Cable Length: 400 mm Voltage Current 12 V DC (Nominal) 0.20 A 7 V DC 0.08 A 5V DC 0.06 A Connection Motherboard: + 12 V DC 3-pin Connector