

# BenQ W2700 4K UHD/ DLP projektor/ HDR/ 2000ANSI/ 30.000:1/ 2x HDMI/ USB

**cena vč DPH: 36686 Kč**

cena bez DPH: 30319 Kč

**Kód zboží (ID): 3826651**

**PN: 9H-JKC77-37E**

**Záruka: 24 měsíců**



Display Projection System DLP Resolution 4K UHD (3840 x 2160) Resolution Support VGA (640 x 480) to 4K UHD (3840 x 2160) Brightness (ANSI lumens) 2000 ANSI Lumens Contrast Ratio (FOFO) 30,000:1 Display Color 30 Bits (1,07 billion colors) Native Aspect Ratio Native 16:9 (6 aspect ratio selectable) Light Source Lamp Light Source Wattage 245W Light Source Life Normal 4,000 hour/Economic 10,000 hours/SmartEco 15,000 hours Optical Throw Ratio 1.13 - 1.47 (100" @ 2.5 m) Zoom Ratio 1.3X Lens F/# = 1.9 - 2.47, f = 12 - 15.6 mm Lens Shift Vertical 100%~110% Keystone Adjustment 1D, (Auto) Vertical  $\pm$  30 degrees Projection Offset 105% Clear Image Size (Diagonal) 40"~200" Image Size 30"~200" Horizontal Frequency 15K-135KHz Vertical Scan Rate 23-120Hz Picture Picture Mode Bright / Vivid TV / Cinema (Rec. 709) / D. Cinema / Silence / User 1 (HDR / HLG / ISF Night / ISF Day / 3D\*) Color Wheel Segment 6-Segment (RGBRGB) Color Wheel Speed 2D: 96Hz ; 100Hz; 120Hz / 3D: 120Hz Rec.709 Coverage 100% DCI-P3 Coverage 95% Audio Speaker Chamber Speaker 5W x 2 Interface HDMI x2 HDMI (2.0a/HDCP2.2) USB Type A x1 (5V/2.5A power) x1 ((Media Reader, FW download) USB Type mini B x1 (FW download, service) Audio out (3.5mm Mini Jack) x1 (mini jack) DC 12V Trigger (3.5mm Jack) x1 (3.5mm Jack) IR Receiver 2 (Front/Top) RS232 x1 Special Feature Motion Enhancer (MEMC) ISF Night/ Day CinemaMaster Video + CinemaMaster Audio+2 Compatibility HDTV Compatibility 720p 50/60Hz, 1080i 50/60Hz, 1080p 24/25/30/50/60Hz, 2160p 23/24/25/30/60Hz 3D Compatibility Power Power Supply VAC 100 ~ 240 (50/60Hz) Typical Power Consumption Max 350W, Normal 340W, Eco 280W Standby Power Consumption 0.5W Max. at 100 ~ 240VAC Acoustic Noise (Typ./Eco.) 30/28dBA (Silence mode) Operating Temperature 0~40 degrees (Celcius) Dimensions and Weight Dimensions (W x H x D)(mm) 380 x 127 x 263 Net Weight (Kg/ lbs ) 4.2 kg / 9.2 lbs Accessories (Standard) Carton Remote Control w/ Battery x 1 (5J.JKC06.001) Power Cord (by region) x 1 (3m) User Manual CD Yes (27L) Quick Start Guide Yes (21L) Warranty Card (by region) Lens cover Accessories

(Optional) Spare Lamp Kit 3D Glasses OSD Language Arabic/ Bulgarian/ Croatian/ Czech/ Danish/ Dutch/ English/ Finnish/ French/ German/ Greek/ Hindi/ Hungarian/ Italian/ Indonesian/ Japanese/ Korean/ Norwegian/ Polish/ Portuguese/ Romanian/ Russian/ Simplified Chinese/ Spanish/ Swedish/ Turkish/ Thai/ Traditional Chinese (28 Languages) \* In 3D Mode: Resolution is 1920x1080 in 3D Mode. \*\* The Contrast is measured by Full On Full Off standard. \*\*\* Lamp life results will vary depending on environmental conditions and usage. Actual product's features and specifications are subject to change without notice.

Display Projection System DLP Resolution 4K UHD (3840 x 2160) Resolution Support VGA (640 x 480) to 4K UHD (3840 x 2160) Brightness (ANSI lumens) 2000 ANSI Lumens Contrast Ratio (FOFO) 30,000:1 Display Color 30 Bits (1,07 billion colors) Native Aspect Ratio Native 16:9 (6 aspect ratio selectable) Light Source Lamp Light Source Wattage 245W Light Source Life Normal 4,000 hour/Economic 10,000 hours/SmartEco 15,000 hours Optical Throw Ratio 1.13 - 1.47 (100" @ 2.5 m) Zoom Ratio 1.3X Lens F/# = 1.9 - 2.47, f = 12 - 15.6 mm Lens Shift Vertical 100%~110% Keystone Adjustment 1D, (Auto) Vertical  $\pm$  30 degrees Projection Offset 105% Clear Image Size (Diagonal) 40"~200" Image Size 30"~200" Horizontal Frequency 15K-135KHz Vertical Scan Rate 23-120Hz Picture Picture Mode Bright / Vivid TV / Cinema (Rec. 709) / D. Cinema / Silence / User 1 (HDR / HLG / ISF Night / ISF Day / 3D\*) Color Wheel Segment 6-Segment (RGBRGB) Color Wheel Speed 2D: 96Hz ; 100Hz; 120Hz / 3D: 120Hz Rec.709 Coverage 100% DCI-P3 Coverage 95% Audio Speaker Chamber Speaker 5W x 2 Interface HDMI x2 HDMI (2.0a/HDCP2.2) USB Type A x1 (5V/2.5A power) x1 ((Media Reader, FW download) USB Type mini B x1 (FW download, service) Audio out (3.5mm Mini Jack) x1 (mini jack) DC 12V Trigger (3.5mm Jack) x1 (3.5mm Jack) IR Receiver 2 (Front/Top) RS232 x1 Special Feature Motion Enhancer (MEMC) ISF Night/ Day CinemaMaster Video + CinemaMaster Audio+2 Compatibility HDTV Compatibility 720p 50/60Hz, 1080i 50/60Hz, 1080p 24/25/30/50/60Hz, 2160p 23/24/25/30/60Hz 3D Compatibility Power Power Supply VAC 100 ~ 240 (50/60Hz) Typical Power Consumption Max 350W, Normal 340W, Eco 280W Standby Power Consumption 0.5W Max. at 100 ~ 240VAC Acoustic Noise (Typ./Eco.) 30/28dBA (Silence mode) Operating Temperature 0~40 degrees (Celcius) Dimensions and Weight Dimensions (W x H x D)(mm) 380 x 127 x 263 Net Weight (Kg/ lbs ) 4.2 kg / 9.2 lbs Accessories (Standard) Carton Remote Control w/ Battery x 1 (5J.JKC06.001) Power Cord (by region) x 1 (3m) User Manual CD Yes (27L) Quick Start Guide Yes (21L) Warranty Card (by region) Lens cover Accessories (Optional) Spare Lamp Kit 3D Glasses OSD Language Arabic/ Bulgarian/ Croatian/ Czech/ Danish/ Dutch/ English/ Finnish/ French/ German/ Greek/ Hindi/ Hungarian/ Italian/ Indonesian/ Japanese/ Korean/ Norwegian/ Polish/ Portuguese/ Romanian/ Russian/ Simplified Chinese/ Spanish/ Swedish/ Turkish/ Thai/ Traditional Chinese (28 Languages) \* In 3D Mode: Resolution is 1920x1080 in 3D Mode. \*\* The Contrast is measured by Full On Full Off standard. \*\*\* Lamp life results will vary depending on environmental conditions and usage. Actual product's features and specifications are subject to change without notice.