

BenQ MU613 WUXGA/ DLP projektor/ 4000 ANSI/ 10000:1/ VGA/ HDMI

cena vč DPH: **21810 Kč**

cena bez DPH: 18025 Kč

Kód zboží (ID): 3876577

PN: 9H-JKX77-13E

Záruka: 36 měsíců



BenQ DLP Projektor MU613 1920x1200 WUXGA/4000 ANSI Lm/1,5÷1,65:1/10000:1/D-Sub/2xHDMI/MHL/RS232/Repro Display Projection System DLP Single 0.47" WUXGA DMD type 0.47" DMD Chip Resolution 1920 x1200 pixels Brightness 4000 ANSI Lumens Contrast Ratio* 10,000:1 Display Color 1.07 Billion Colors Aspect Ratio Native 16:10 (5 aspect ratio selectable) Light Source Lamp Light Source Life?* 4000/10000/8000/15000 hours(Normal/Eco/SmartEco/Lamp save mode) Optical Throw Ratio 1.5~1.65 Zoom Ratio 1.1X Lens Control Manual Zoom and Focus Lens shift N/A Keystone Correction Vertical: ± 40 degrees Projection Offset 100%±3% Projection Size 30" ~ 300" Audio Built-in Speaker 2W Special Feature Security Security Bar,Kingston lock Feature Optional Wireless Presentation, Dual HDMI Connectivity I/O Port HDMI-1 X 1 HDMI-2/MHL X 1 USB TypeA(1.5A power) X 1 Computer In (D-sub 15pin, Female) X 1 Monitor out (D-sub 15pin,Female) X 1 RS232 In (D-sub 9pin, male) X 1 Audio in(mini jack) X 1 Audio out(mini jack) X 1 IR Receiver(Front+Rear) X 2 Compatibility Resolution Support VGA(640 x 480) to WUXGA_RB(1920X1200) *RB=Reduced blanking Horizontal Frequency 15~102KHz Vertical Scan Rate 23 ~ 120 Hz HDTV Compatibility 480i, 480p, 576i, 567p, 720p, 1080i, 1080p Video Compatibility N/A Power Power Consumption(Max/Normal/Eco) 260W/110V Standby Power Consumption Normal < 0.5Watts. Power Supply 100 ~ 240V AC Dimension and Weight Product Dimensions (WxHxD) W 312 x D 225 x H 110 X 222mm Product Weight 2.63kg ± 100g Operation Condition Noise Level(Normal/Eco) 35/29 dBA Operating Temperature 0 °C ~ 40 °C Accessories (Standard) Remote control (5J.JGV06.001) AAA Batteryx2 Power Cord (by region) VGA cable Warranty Card (by region) QSG (4J.JKW01.001) User Manual CD (5B.JKW01.001) Accessories (Optional) Spare Lamp Kit (5J.JHH05.001) RS232 Cable 3D Glasses (5J.J9H25.002) Wireless Dongle - QCast Mirror QP20 (5A.JH328.10X) Wireless Dongle - QCast QP01 (5J.JCK28.X01) Wireless Kit - InstaShow WDC10 (5J.JF828.X30) Ceiling mount (5J.JAM10.001) OSD On Screen Display Language

Arabic/Bulgarian/ Croatian/ Czech/ Danish/ Dutch/ English/ Finnish/ French/ German/ Greek/ Hindi/ Hungarian/ Italian/ Indonesian/ Japanese/ Korean/ Norwegian/ Polish/ Portuguese/ Romanian/ Russian/ Simplified Chinese/Spanish/ Swedish/ Turkish/ Thai/ Traditional Chinese / Vietnamese/ Persian (30 Languages) Environment Notice
*LightSource life results will vary depending on environmental conditions and usage. Actual product's features and specifications are subject to change without notice. * The Contrast is measure by Full On Full Off standard.

BenQ DLP Projektor MU613 1920x1200 WUXGA/4000 ANSI Lm/1,5÷1,65:1/10
000:1/D-Sub/2xHDMI/MHL/RS232/Repro Display Projection System DLP Single 0.47"
WUXGA DMD type 0.47" DMD Chip Resolution 1920 x1200 pixels Brightness 4000
ANSI Lumens Contrast Ratio* 10,000:1 Display Color 1.07 Billion Colors Aspect
Ratio Native 16:10 (5 aspect ratio selectable) Light Source Lamp Light Source
Life?* 4000/10000/8000/15000 hours(Normal/Eco/SmartEco/Lamp save mode)
Optical Throw Ratio 1.5~1.65 Zoom Ratio 1.1X Lens Control Manual Zoom and
Focus Lens shift N/A Keystone Correction Vertical: ± 40 degrees Projection Offset
100%±3% Projection Size 30" ~ 300" Audio Built-in Speaker 2W Special Feature
Security Security Bar,Kingston lock Feature Optional Wireless Presentation, Dual
HDMI Connectivity I/O Port HDMI-1 X 1 HDMI-2/MHL X 1 USB TypeA(1.5A power) X 1
Computer In (D-sub 15pin, Female) X 1 Monitor out (D-sub 15pin,Female) X 1
RS232 In (D-sub 9pin, male) X 1 Audio in(mini jack) X 1 Audio out(mini jack) X 1 IR
Receiver(Front+Rear) X 2 Compatibility Resolution Support VGA(640 x 480) to
WUXGA_RB(1920X1200) *RB=Reduced blanking Horizontal Frequency 15~102KHz
Vertical Scan Rate 23 ~ 120 Hz HDTV Compatibility 480i, 480p, 576i, 567p, 720p,
1080i, 1080p Video Compatibility N/A Power Power Comsumption(Max/Normal/Eco)
260W/110V Standby Power Comsumption Normal < 0.5Watts. Power Supply 100
~ 240V AC Dimension and Weight Product Dimensions (WxHxD) W 312 x D 225 x H
110 X 222mm Product Weight 2.63kg ± 100g Operation Condition Noise
Level(Normal/Eco) 35/29 dBA Operating Temperature 0 °C ~ 40 °C Accessories
(Standard) Remote control (5J.JGV06.001) AAA Batteryx2 Power Cord (by region)
VGA cable Warranty Card (by region) QSG (4J.JKW01.001) User Manual CD
(5B.JKW01.001) Accessories (Optional) Spare Lamp Kit (5J.JHH05.001) RS232 Cable
3D Glasses (5J.J9H25.002) Wireless Dongle - QCast Mirror QP20 (5A.JH328.10X)
Wireless Dongle - QCast QP01 (5J.JCK28.X01) Wireless Kit - InstaShow WDC10
(5J.JF828.X30) Ceiling mount (5J.JAM10.001) OSD On Screen Display Language
Arabic/Bulgarian/ Croatian/ Czech/ Danish/ Dutch/ English/ Finnish/ French/
German/ Greek/ Hindi/ Hungarian/ Italian/ Indonesian/ Japanese/ Korean/
Norwegian/ Polish/ Portuguese/ Romanian/ Russian/ Simplified Chinese/Spanish/
Swedish/ Turkish/ Thai/ Traditional Chinese / Vietnamese/ Persian (30 Languages)
Environment Notice *LightSource life results will vary depending on environmental
conditions and usage. Actual product's features and specifications are subject to
change without notice. * The Contrast is measure by Full On Full Off standard.