

SUPERMICRO 2U chassis 8x 3,5" HS SAS3/SATA, 2x800W (80PLUS Titanium)

cena vč DPH: **23183 Kč**

cena bez DPH: 19160 Kč

Kód zboží (ID): 4346485

PN: CSE-825TQC-
R802LPB

Záruka: 36 měsíců



Product SKUs CSE-825TQC-R802LPB SuperChassis 825TQC-R802LPB Form Factor 2U chassis supports for maximum motherboard sizes - 13.68" x 13", E-ATX 12" x 13", ATX 12" x 10" motherboards Processor Support Dual and Single Intel® and AMD processors Dimensions Height 3.5" (89 mm) Width 17.2" (437 mm) Depth 25.5" (647 mm) Gross Weight 52 lbs (23.59 kg) Packaging (W x H x L) 26.7" (678 mm) x 11.4" (290 mm) x 34.5" (876 mm) Available Color Black Expansion Slots 7 low-profile expansion slot(s) Drive Bays 8 x 3.5" hot-swap SAS3/SATA drive bay 2 x 3.5" fixed drive bay Backplane 8-port 2U SAS3 12Gbps TQ backplane, support up to 8x 3.5-inch SAS3/SATA3 HDD/SSD Peripheral Drives Optional 1 x slim DVD-ROM drive bay Optional 2 x USB 2.0 ports Optional 1 x COM port tray Optional 2 x USB 3.0 ports Front Panel Buttons Power On/Off button System Reset Button LEDs 2 Network Activity LEDs HDD activity LED Power Status LED Power Fail LED System Information LED Systems Cooling Fans 3 x 80mm Hot-swap PWM Fans System Monitoring Chassis intrusion switch Operating Environment (System) Operating Temperature Range 5°C - 35°C (41°F - 95°F) Non-Operating Temperature Range -40°C - 70°C (-40°F - 158°F) Operating Relative Humidity Range 8% - 90% (non-condensing) Non-Operating Relative Humidity Range 5% - 95% (non-condensing) Power Supply 1U 800W Redundant Power Supply 76mm width, W/PMbus, Titanium Power Efficiency 96% Total Output Power and Input 800W with Input 100 - 240Vac 800W with Input 200 - 240Vdc AC Input Frequency 50-60Hz Dimensions (L x W x H) 336 x 76 x 40 mm Output Type Backplanes (gold finger) +12V Max: 66A (100Vac - 240Vac) Max: 66A (200 - 240) +5Vsb Max: 4A / Min: 0A Power Distributor PDB-PT825-8824 O/P: 12V/75 +5V Max: 30 +3.3V Max: 24 -12V Max: 0.6 Certification Titanium Certified Titanium Certified Regulatory (Power Supply) Power Supply Safety / EMC BSMI CCC CE/EMC FCC class A TUV/CB UL/CUL Components ? Standard Parts List Part Number Qty Description Air Shroud MCP-310-29001-0N 1 SC825/826/216/213 Intel DP X9,X8

air shroud 13.68x13/12x13 HD Backplane BPN-SAS3-825TQ 1 8-port 2U SAS3 12Gbps TQ backplane, support up to 8x 3.5-inch SAS3/SATA3 HDD/SSD Cable(S) CBL-0071L 1 ROUND 16 TO 16 PIN RIBBON FP CABLE 30"L, LF Cable(S) CBL-0160L 2 US POWER CORD 16AWG, PB FREE CD-ROM & Accessory MCP-290-00007-01 1 Black DVD dummy cover for SC825, 836 Fan(s) FAN-0181L4 3 80x80x38 mm, 9.4K RPM, Hot-swappable Middle Cooling Fan for X11 Purley Platform Newly Enabled 2U+ Chassis Front Panel FPB-FP836-D 1 Front control board Dual color LED(FP836-D)forSC823M,825,825M,828,829,835,836 Drive Tray(s) MCP-220-00023-01 1 Black USB dummy tray support 1x 2.5" slim HDD for SC825, 836 Drive Tray(s) MCP-220-00075-0B 8 Black gen 5.5 hot-swap 3.5" HDD tray Drive Tray(s) MCP-220-82502-0B 2 Black fixed 3.5" HDD tray or FDD dummy tray Power Distributor PDB-PT825-8824 1 SC825 24PIN REDUNDANT POWER DISTRIBUTOR Power Supply & Accessory PWS-802A-1R 2 1U 800W 100-240Vac/47-63Hz, and DC240 input Mounting Rail(s) MCP-290-00053-0N 1 Rail set, quick/quick, default for 2,3U 17.2";W Rear Window MCP-240-82506-0N 1 LP Rear Window for SC825,825M,826,213,216 Optional Parts List Part Number Qty Description Adaptor Bracket MCP-120-82503-0N - Cable arm adapter for SC825LP,213LP (MCP-290-00073-0N required),HF,RoHS/REACH,PBF Cable Management Arm MCP-290-00073-0N - Supermicro Cable Management Arm for 2U, 3U and 4U chassis Rail MCP-290-00058-0N - Short rail set, quick release, 19.6"~26.9" Extendable Length Front USB MCP-220-00007-01 - Black USB/COM port tray for SC825, 836 Front USB MCP-220-00114-0N - Black 2x USB3.0/COM port tray in slim DVD bay,RoHS/REACH Tray(s) MCP-290-00036-0B - Black DVD dummy tray support 1x2.5 HDD for SC113,815,825,836 Tray(s) MCP-220-00023-01 - Black USB dummy tray support 1x 2.5" slim HDD for SC825, 836 Tray(s) MCP-220-82503-0B - Black slim FDD kit for SC825/829,828,835 Cable CBL-0157L - 8 pin to 8 pin ribbon SGPIO cable with tube , 40cm, PBF Cable CBL-SAST-0699 - internal mini SAS HD to 4 SATA 12G, 75/75/90/90cm w/75cm SB, S. 30AWG,RoHS/REACH Cable CBL-0082L - Y split , big 4 pin to two RA SATA power extension 15cm, 18AWG Cable CBL-0296L - 4 pin to 4 pin fan extension cord, for PWM fan. 23cm. 24AWG Cable CBL-0180L-01 - SET OF 4 SATA 70/59/48/38CM ROUND S-RA, 26AWG LCD/OLED Solutions MCP-220-00119-0B - 2nd Gen Black 3.5" OLED tray, support 1x internal 2.5" HDD SATA DVD Kit MCP-220-81502-0N - Slim SATA DVD mounting kit for SC213,219,813,815,818,819,825,828,829,836,842 HDD Tray Converter MCP-220-00043-0N - Black hot-swap gen 4 3.5 to 2.5 HDD tray DVD-ROM / DVD-RW DVM-TEAC-DVD-SBT5 - BLACK TEAC SLIM DVD SATA DRIVE,HF,RoHS SATA DVD Kit MCP-220-81502-0N - Slim SATA DVD mounting kit for SC213,219,813,815,818,819,825,828,829,836,842 Peripheral Drive(s) FPD-TEAC-SB - BLACK SLIM TEAC FLOPPY DRIVE FOR SC813 Front Bezel MCP-210-82503-0B - Black SC825 front bezel Motherboard (for CSE- 825TQC-R802LPB) H11DSI-NT H11DSi X11SSL-F X11SSL X11SSM-F X11SSM X11SCM-F X11SCM-LN8F

Product SKUs CSE-825TQC-R802LPB SuperChassis 825TQC-R802LPB Form Factor 2U chassis supports for maximum motherboard sizes - 13.68" x 13", E-ATX 12" x 13", ATX 12" x 10" motherboards Processor Support Dual and Single Intel® and

AMD processors Dimensions Height 3.5" (89 mm) Width 17.2" (437 mm) Depth 25.5" (647 mm) Gross Weight 52 lbs (23.59 kg) Packaging (W x H x L) 26.7" (678 mm) x 11.4" (290 mm) x 34.5" (876 mm) Available Color Black Expansion Slots 7 low-profile expansion slot(s) Drive Bays 8 x 3.5" hot-swap SAS3/SATA drive bay 2 x 3.5" fixed drive bay Backplane 8-port 2U SAS3 12Gbps TQ backplane, support up to 8x 3.5-inch SAS3/SATA3 HDD/SSD Peripheral Drives Optional 1 x slim DVD-ROM drive bay Optional 2 x USB 2.0 ports Optional 1 x COM port tray Optional 2 x USB 3.0 ports Front Panel Buttons Power On/Off button System Reset Button LEDs 2 Network Activity LEDs HDD activity LED Power Status LED Power Fail LED System Information LED Systems Cooling Fans 3 x 80mm Hot-swap PWM Fans System Monitoring Chassis intrusion switch Operating Environment (System) Operating Temperature Range 5°C - 35°C (41°F - 95°F) Non-Operating Temperature Range -40°C - 70°C (-40°F - 158°F) Operating Relative Humidity Range 8% - 90% (non-condensing) Non-Operating Relative Humidity Range 5% - 95% (non-condensing) Power Supply 1U 800W Redundant Power Supply 76mm width, W/PMbus, Titanium Power Efficiency 96% Total Output Power and Input 800W with Input 100 - 240Vac 800W with Input 200 - 240Vdc AC Input Frequency 50-60Hz Dimensions (L x W x H) 336 x 76 x 40 mm Output Type Backplanes (gold finger) +12V Max: 66A (100Vac - 240Vac) Max: 66A (200 - 240) +5Vsb Max: 4A / Min: 0A Power Distributor PDB-PT825-8824 O/P: 12V/75 +5V Max: 30 +3.3V Max: 24 -12V Max: 0.6 Certification Titanium Certified Titanium Certified Regulatory (Power Supply) Power Supply Safety / EMC BSMI CCC CE/EMC FCC class A TUV/CB UL/CUL Components ?

Standard Parts List Part Number Qty Description Air Shroud MCP-310-29001-0N 1 SC825/826/216/213 Intel DP X9,X8 air shroud 13.68x13/12x13 HD Backplane BPN-SAS3-825TQ 1 8-port 2U SAS3 12Gbps TQ backplane, support up to 8x 3.5-inch SAS3/SATA3 HDD/SSD Cable(S) CBL-0071L 1 ROUND 16 TO 16 PIN RIBBON FP CABLE 30"L, LF Cable(S) CBL-0160L 2 US POWER CORD 16AWG, PB FREE CD-ROM & Accessory MCP-290-00007-01 1 Black DVD dummy cover for SC825, 836 Fan(s) FAN-0181L4 3 80x80x38 mm, 9.4K RPM, Hot-swappable Middle Cooling Fan for X11 Purley Platform Newly Enabled 2U+ Chassis Front Panel FPB-FP836-D 1 Front control board Dual color LED(FP836-D)forSC823M,825,825M,828,829,835,836 Drive Tray(s) MCP-220-00023-01 1 Black USB dummy tray support 1x 2.5" slim HDD for SC825, 836 Drive Tray(s) MCP-220-00075-0B 8 Black gen 5.5 hot-swap 3.5" HDD tray Drive Tray(s) MCP-220-82502-0B 2 Black fixed 3.5" HDD tray or FDD dummy tray Power Distributor PDB-PT825-8824 1 SC825 24PIN REDUNDANT POWER DISTRIBUTOR Power Supply & Accessory PWS-802A-1R 2 1U 800W 100-240Vac/47-63Hz, and DC240 input Mounting Rail(s) MCP-290-00053-0N 1 Rail set, quick/quick, default for 2,3U 17.2";W Rear Window MCP-240-82506-0N 1 LP Rear Window for SC825,825M,826,213,216 Optional Parts List Part Number Qty Description Adaptor Bracket MCP-120-82503-0N - Cable arm adapter for SC825LP,213LP (MCP-290-00073-0N required),HF,RoHS/REACH,PBF Cable Management Arm MCP-290-00073-0N - Supermicro Cable Management Arm for 2U, 3U and 4U chassis Rail MCP-290-00058-0N - Short rail set, quick release, 19.6"~26.9" Extendable Length Front USB MCP-220-00007-01 - Black USB/COM port tray for SC825, 836 Front USB MCP-220-00114-0N - Black 2x USB3.0/COM port tray in slim DVD bay,RoHS/REACH Tray(s) MCP-290-00036-0B - Black DVD dummy tray support 1x2.5 HDD for SC113,815,825,836 Tray(s) MCP-220-00023-01 - Black USB dummy tray support 1x 2.5" slim HDD for SC825, 836 Tray(s) MCP-220-82503-0B - Black slim FDD kit for SC825/829,828,835 Cable CBL-0157L -

8 pin to 8 pin ribbon SGPIO cable with tube , 40cm, PBF Cable CBL-SAST-0699 - internal mini SAS HD to 4 SATA 12G, 75/75/90/90cm w/75cm SB, S.
30AWG,RoHS/REACH Cable CBL-0082L - Y split , big 4 pin to two RA SATA power extension 15cm, 18AWG Cable CBL-0296L - 4 pin to 4 pin fan extension cord, for PWM fan. 23cm. 24AWG Cable CBL-0180L-01 - SET OF 4 SATA 70/59/48/38CM ROUND S-RA, 26AWG LCD/OLED Solutions MCP-220-00119-0B - 2nd Gen Black 3.5" OLED tray, support 1x internal 2.5" HDD SATA DVD Kit MCP-220-81502-0N - Slim SATA DVD mounting kit for SC213,219,813,815,818,819,825,828,829,836,842 HDD Tray Converter MCP-220-00043-0N - Black hot-swap gen 4 3.5 to 2.5 HDD tray DVD-ROM / DVD-RW DVM-TEAC-DVD-SBT5 - BLACK TEAC SLIM DVD SATA DRIVE,HF,RoHS SATA DVD Kit MCP-220-81502-0N - Slim SATA DVD mounting kit for SC213,219,813,815,818,819,825,828,829,836,842 Peripheral Drive(s) FPD-TEAC-SB - BLACK SLIM TEAC FLOPPY DRIVE FOR SC813 Front Bezel MCP-210-82503-0B - Black SC825 front bezel Motherboard (for CSE- 825TQC-R802LPB) H11DSI-NT H11DSi X11SSL-F X11SSL X11SSM-F X11SSM X11SCM-F X11SCM-LN8F