

# SCYTHE KF1215FD18 Kaze Flex 120 mm Slim Fan 1800 RPM

**cena vč DPH:** **452 Kč**

**cena bez DPH:** 373 Kč

**Kód zboží (ID):** 4358200

**PN:** KF1215FD18

**Záruka:** 24 měsíců



Scythe Kaze Flex 120 Slim The bearing structure of FDB (Fluid Dynamic Bearing) is made of high quality compressed metal, which contributes to low friction and a long life span High quality lubricant oil enclosed between shaft and bearing withstands temperatures of up to 250°C and results in an excellent lubricating effect Vibration and shock absorbing rubber pads are integrated into the fans design and further enhance a silent operation, making this fan ideal for cases and coolers

Specifications Model Name: Kaze Flex 120 Slim Model-Nr.: KF1215FD18 Dimensions: 120 x 120 x 17 mm Fan Speed: 1800 rpm ( $\pm 10\%$ ) Noise Level: 30 dBA Airflow: 50.79 CFM = 86.5=25 m<sup>3</sup>/h Static Pressure: 1,35 mmH<sub>2</sub>O = 13,24 Pa Voltage: 12 V Amperage: 0,18 A Power Input: 2,16 W Connector: 3-pin Accessory: Molex-Adaptor, 4x screws, Bearing: Sealed Precision Fluid Dynamic Bearing MTTF: 100.000 Hours (25°C)

Scythe Kaze Flex 120 Slim The bearing structure of FDB (Fluid Dynamic Bearing) is made of high quality compressed metal, which contributes to low friction and a long life span High quality lubricant oil enclosed between shaft and bearing withstands temperatures of up to 250°C and results in an excellent lubricating effect Vibration and shock absorbing rubber pads are integrated into the fans design and further enhance a silent operation, making this fan ideal for cases and coolers Specifications Model Name: Kaze Flex 120 Slim Model-Nr.: KF1215FD18 Dimensions: 120 x 120 x 17 mm Fan Speed: 1800 rpm ( $\pm 10\%$ ) Noise Level: 30 dBA Airflow: 50.79 CFM = 86.5=25 m<sup>3</sup>/h Static Pressure: 1,35 mmH<sub>2</sub>O = 13,24 Pa Voltage: 12 V Amperage: 0,18 A Power Input: 2,16 W Connector: 3-pin Accessory:

Molex-Adaptor, 4x screws, Bearing: Sealed Precision Fluid Dynamic Bearing MTTF:  
100.000 Hours (25°C)