

ASRock Rack ROMED8-2T 1x SP3, 8x DDR4 ECCreg, 9x SATA, 2x M.2(22110,2280), 7x PCIe4 x16, 2x 10Gb LAN, IPMI

cena vč DPH: 19946 Kč

cena bez DPH: 16485 Kč

Kód zboží (ID): 4378402

PN: ROMED8-2T

Záruka: 36 měsíců



The specification is subject to change without notice in advance. The brand and product names are trademarks of their respective companies. Any configuration other than original product specification is not guaranteed.

$\langle p \rangle$

 ATX 12" x 9.6"

 & Single Socket SP3 (LGA4094) support AMD EPYC™ 7002/7001 series processor family

 Supports 8 Channels DDR4 3200/2933/2666/2400

- Supports Energy Efficient Ethernet 802.3az
- Supports Dual LAN with Teaming function
- Supports PXE
- LAN1 supports NCSI

Management

BMC Controller - ASPEED AST2500

IPMI Dedicated GLAN - 1 x Realtek RTL8211E for dedicated management GLAN

Features - Watch Dog

- NMI

Graphics

Controller - ASPEED AST2500

VRAM - DDR4 512MB

Rear Panel I/O

VGA Port - 1 x D-Sub

USB 3.1 Gen1 Port - 2

USB 3.1 Gen2 Port - 1 (Type C)

Lan Port - 2+1 RJ45 Gigabit Ethernet LAN port

- LAN Ports with LED (ACT/LINK LED and SPEED LED)

Serial Port - 1 x COM port

UID Button/UID LED - 1

Internal Connector

SATA DOM - 1 (BOM option)

M.2 - 2 (M2_1 (share with PCIE2 by Jumper): 2230/2242/2260/2280, SATA/PCIE Gen4(X4); M2_2: 2230/2242/2260/2280/22110, SATA/PCIE(X4))

Auxiliary Panel Header - 1 (includes chassis intrusion, location button & LED, and front LAN LED)

TR1 Header - 1

TPM Header - 1

IPMB Header - 1

Fan Header - 7 Fans x 6-pin (1CPU/4Front/2Rear)

ATX Power - 1 x (24-pin) + 1 x (8-pin) + 1 x (4-pin) + 1 x (6-pin) (6 pin for GPU for PCIE Slot)

USB 3.1 (Gen1) Header - 1 (supports 2 USB 3.0 ports)

USB 3.1 (Gen2) Header - 1 (supports 2 USB 3.0 ports)

NMI Button - 1

Front Panel - 1 (rst, pwrbtn, hddled, pwrled)

Speaker Header - 1 (4pin)

BMC_SMB Header - 1

Clear CMOS - 1

PSU SMB Header - 1

Onboard LED

Fan Fail LED - 7

System BIOS

BIOS Type - 32MB AMI UEFI Legal BIOS

BIOS Features - Plug and Play (PnP)

- ACPI 2.0 Compliance Wake Up Events
- SMBIOS 2.8 Support
- ASRock Rack Instant Flash

 Hardware Monitor

Temperature - CPU Temperature Sensing

- MB/TR1/Card side Temperature Sensing

Fan - CPU/Rear/Front Fan Tachometer

- CPU Quiet Fan (Allow CPU Fan Speed Auto-Adjust by CPU Temperature)

- CPU/Rear/Front Fan Multi-Speed Control

Voltage - Voltage Monitoring: Vsoc,Vcpu, VCCM, VPPM, 3V/5V/12V, +BAT, 3VSB, 5VSB

 Environment

Temperature Operation temperature: 10°C ~ 35°C / Non operation temperature: -40°C ~ 70°C</p>

<p>The specification is subject to change without notice in advance. The brand and product names are trademarks of their respective companies. Any configuration other than original product specification is not guaranteed.</p>

<p> </p>

<p> </p>