

BenQ DLP Projektor MW560 /1280x800 WXGA/4000 ANSI/1.55÷1.7:1/20k:1/2xHDMI/ VGA/S-Video/Composite/USB/10W repro

cena vč DPH: **12157 Kč**

cena bez DPH: 10048 Kč

Kód zboží (ID): 4564209

PN: 9H-JNF77-13E

Záruka: 36 měsíců



All Specifications Display Projection System DLP Single 0.65" WXGA Resolution 1280 x 800 pixels Resolution Support VGA(640 x 480) to WUXGA_RB(1920 x 1200) Brightness (ANSI lumens) 4000 ANSI Lumens Contrast Ratio (FOFO) 20000:1 Display Color 30 Bits (1,07 billion colors) Native Aspect Ratio Native 16:9 (5 aspect ratio selectable) Light Source Lamp Light Source life* Normal 6000 hr Economic 10000 hr SmartEco 10000 hr LampSave 15000hr Optical Throw Ratio 1.55÷1.7 (87" ±3% @ 2.9m) Zoom Ratio 1.1X Lens shift NA Projection Offset** 100%±2.5% (Full-Height) Projection Size 60"~150" Keystone Correction Auto ID, Vertical +/- 40 degrees Audio Speaker 10W x 1 Special Feature Security Security Bar, Kensington lock Feature 1D Auto Keystone, High Brightness, Spreadsheet mode, Bright Mode, Presentation Mode, Infographic Mode, Video Mode, Srgb Mode Compatibility Resolution Support VGA(640 x 480) to WUXGA_RB(1920 x 1200) Horizontal Frequency 15K~102KHz Vertical Scan Rate 23 ~ 120 Hz HDTV Compatibility 480i, 480p, 576i, 567p, 720p, 1080i, 1080p Video Compatibility NTSC, PAL, SECAM, SDTV (480i/576i), EDTV (480p/576p), HDTV (720p, 1080i/p 60Hz) Connectivity HDMI HDMI-1 x1 HDMI-2 x1 PC (D-sub 15pin) 1 Monitor out (D-sub 15pin,Female) 1 Audio in (mini jack) 1 Audio out (mini jack) 1 RS232 In (D-sub 9pin, male) 1 USB TypeA-1 x1 (1.5A power) USB Type mini B x1 IR Receiver (Front+Top) 2 S-Video x1 Composite Video (RCA) x1 Dimension and Weight Dimensions (W x H x D)(mm) 296 x 120 x 221 mm Net Weight (Kg/ lbs) 2.3kg +/- 200g Power Power Consumption(Max/Normal/Eco) Max 280W, Normal 260W, Eco 215W Standby Power Consumption Normal < 0.5Watts. Power Supply 100 ~ 240V AC Operation Condition Noise Level(Normal/Eco) 34 /29 dBA Operating Temperature 0~40 °C Accessories (Standard) Remote Control w/ Battery x 1 (5J.JND06.001) Power Cord (by region) x 1 (1.8m) Warranty Card (by region) x 1 VGA(D-sub 15pin) Cable x 1 (1.5m) AAA

Battery x2 QSG x1 (4J.JND01.001) Accessories (Optional) Spare Lamp Kit x 1 (5J.JND05.001) Universal Ceiling Mount x 1 3D Glasses x 1 (5J.J9H25.002) QCast Mirror dongle x 1 (5A.JH328.10X) OSD OSD Language Arabic/Bulgarian/ Croatian/ Czech/ Danish/ Dutch/ English/ Finnish/ French/ German/ Greek/ Hindi/ Hungarian/ Italian/ Indonesian/ Japanese/ Korean/ Norwegian/ Polish/ Portuguese/ Romanian/ Russian/ Simplified Chinese/Spanish/ Swedish/ Turkish/ Thai/ Traditional Chinese/ Farsi / Vietnamese/ (30 Languages)

All Specifications Display Projection System DLP Single 0.65" WXGA Resolution 1280 x 800 pixels Resolution Support VGA(640 x 480) to WUXGA_RB(1920 x 1200) Brightness (ANSI lumens) 4000 ANSI Lumens Contrast Ratio (FOFO) 20000:1 Display Color 30 Bits (1,07 billion colors) Native Aspect Ratio Native 16:9 (5 aspect ratio selectable) Light Source Lamp Light Source life* Normal 6000 hr Economic 10000 hr SmartEco 10000 hr LampSave 15000hr Optical Throw Ratio 1.55÷1.7 (87" ±3% @ 2.9m) Zoom Ratio 1.1X Lens shift NA Projection Offset** 100%±2.5% (Full-Height) Projection Size 60"~150" Keystone Correction Auto ID, Vertical +/- 40 degrees Audio Speaker 10W x 1 Special Feature Security Security Bar, Kensington lock Feature 1D Auto Keystone, High Brightness, Spreadsheet mode, Bright Mode, Presentation Mode, Infographic Mode, Video Mode, Srgb Mode Compatibility Resolution Support VGA(640 x 480) to WUXGA_RB(1920 x 1200) Horizontal Frequency 15K~102KHz Vertical Scan Rate 23 ~ 120 Hz HDTV Compatibility 480i, 480p, 576i, 567p, 720p, 1080i, 1080p Video Compatibility NTSC, PAL, SECAM, SDTV (480i/576i), EDTV (480p/576p), HDTV (720p, 1080i/p 60Hz) Connectivity HDMI HDMI-1 x1 HDMI-2 x1 PC (D-sub 15pin) 1 Monitor out (D-sub 15pin,Female) 1 Audio in (mini jack) 1 Audio out (mini jack) 1 RS232 In (D-sub 9pin, male) 1 USB TypeA-1 x1 (1.5A power) USB Type mini B x1 IR Receiver (Front+Top) 2 S-Video x1 Composite Video (RCA) x1 Dimension and Weight Dimensions (W x H x D)(mm) 296 x 120 x 221 mm Net Weight (Kg/ lbs) 2.3kg +/- 200g Power Power Consumption(Max/Normal/Eco) Max 280W, Normal 260W, Eco 215W Standby Power Consumption Normal < 0.5Watts. Power Supply 100 ~ 240V AC Operation Condition Noise Level(Normal/Eco) 34 /29 dBA Operating Temperature 0~40 °C Accessories (Standard) Remote Control w/ Battery x 1 (5J.JND06.001) Power Cord (by region) x 1 (1.8m) Warranty Card (by region) x 1 VGA(D-sub 15pin) Cable x 1 (1.5m) AAA Battery x2 QSG x1 (4J.JND01.001) Accessories (Optional) Spare Lamp Kit x 1 (5J.JND05.001) Universal Ceiling Mount x 1 3D Glasses x 1 (5J.J9H25.002) QCast Mirror dongle x 1 (5A.JH328.10X) OSD OSD Language Arabic/Bulgarian/ Croatian/ Czech/ Danish/ Dutch/ English/ Finnish/ French/ German/ Greek/ Hindi/ Hungarian/ Italian/ Indonesian/ Japanese/ Korean/ Norwegian/ Polish/ Portuguese/ Romanian/ Russian/ Simplified Chinese/Spanish/ Swedish/ Turkish/ Thai/ Traditional Chinese/ Farsi / Vietnamese/ (30 Languages)