

ASUS TUF GAMING B550M-PLUS WIFI II / B550 / AM4 / 4x DIMM / M.2 / DP / HDMI / mATX

cena vč DPH: **3794 Kč**

cena bez DPH: 3135 Kč

Kód zboží (ID): 5271971

PN: 90MB19Y0-M0EAY0

Záruka: 36 měsíců



ATX gaming motherboard with PCIe 4.0, dual M.2, 10 DrMOS power stages, Wi-Fi 6, 2.5 Gb Ethernet, HDMI, DisplayPort, SATA 6 Gbps, USB 3.2 Gen 2 Type-A and Type-C®, BIOS FlashBack™, and Aura Sync RGB lighting support AMD AM4 socket: Ready for Ryzen™ 5000 Series/ 5000 G-Series/ 4000 G-Series/ 3000 Series Desktop Processors Enhanced power solution: 8+2 DrMOS power stages, ProCool connector, military-grade TUF components, and DIGI+ VRM for maximum durability Comprehensive cooling: VRM heatsinks, PCH fanless heatsink, M.2 heatsink, hybrid fan headers and Fan Xpert 2+ utility Ultrafast connectivity: PCIe 4.0 M.2, USB 3.2 Gen 2 Type-A and Type-C® support Made for online gaming: Wi-Fi 6, Realtek 2.5Gb Ethernet, and TUF LANGuard Two-Way AI Noise Cancelation: Reduces background noise from the microphone and audio output for crystal-clear communication in games or video conferences Chipset: B550 Rozměrový formát: microATX (24.4cm x 24.4cm) Podpora pro procesory: AMD Ryzen 5000 Series/ 5000 G-Series/ 4000 G-Series/ 3000 Series Desktop Processors Pozice na paměti: 4 x DIMM DDR4, Dual Channel Memory Architecture Podpora pro paměti: DDR4 4866(OC)/4800(OC)/4600(OC)/4466(OC)/4400(OC)/4333(OC)/4266(OC)/4200(OC)/4133(OC)/4000(OC)/3866(OC)/3733(OC)/3600(OC)/3466(OC)/3400(OC)/3333(OC)/3200/3000/2933/2800/2666/2400/2133 MHz Max.velikost operační paměti: 128 GB Podpora pro paměti typu: ECC Grafická karta: (na základě procesoru) 1 x DisplayPort 1 x HDMI port Zvuková karta: Realtek 7.1 Surround Sound High Definition Audio CODEC Síťová karta: TUF LANGuard Wi-Fi 6 (802.11 a/b/g/n/ac/ax) Bluetooth 5.2 Rozšiřující sloty: AMD Ryzen 5000 Series/ 3000 Series Desktop Processors 1 x PCIe 4.0 x16 slot (supports x16 mode) AMD Ryzen 5000 G-Series/ 4000 G-Series Desktop Processors 1 x PCIe 3.0 x16 slot (supports x16 mode) AMD B550 Chipset 1 x PCIe 3.0 x16 slot (supports x4 mode) 1 x PCIe 3.0 x1 slot RAID řadič: RAID 0, 1, 10 SATA: 4 x SATA 6Gb/s ports

M.2: 2 x M.2 slots (Key M) USB: Interní: 1 x USB 3.2 Gen 1 header supports additional 2 USB 3.2 Gen 1 ports 2 x USB 2.0 headers support additional 4 USB 2.0 ports Externí: 2 x USB 3.2 Gen 2 ports (1 x Type-A + 1 x USB Type-C) 4 x USB 3.2 Gen 1 ports (4 x Type-A, one port can be switched to USB BIOS FlashBack™) 2 x USB 2.0 ports (2 x Type-A) Interní porty: Fan and Cooling related 1 x 4-pin CPU Fan header 1 x 4-pin CPU OPT Fan header 2 x 4-pin Chassis Fan headers Power related: 1 x 24-pin Main Power connector 1 x 8-pin +12V Power connector Storage related: 2 x M.2 slots (Key M) 4 x SATA 6Gb/s ports USB 1 x USB 3.2 Gen 1 header supports additional 2 USB 3.2 Gen 1 ports 2 x USB 2.0 headers support additional 4 USB 2.0 ports Miscellaneous: 1 x Addressable Gen 2 header 2 x AURA RGB headers 1 x Clear CMOS header 1 x COM Port header 1 x Front Panel Audio header (AAFP) 1 x Speaker header 1 x SPI TPM header (14-1pin) 1 x 10-1 pin System Panel header Externí porty: 2 x USB 3.2 Gen 2 ports (1 x Type-A + 1 x USB Type-C) 4 x USB 3.2 Gen 1 ports (4 x Type-A, one port can be switched to USB BIOS FlashBack) 2 x USB 2.0 ports (2 x Type-A) 1 x DisplayPort 1 x HDMI port 1 x Wi-Fi Module 1 x Realtek 2.5Gb Ethernet port 5 x Audio jacks 1 x Optical S/PDIF out port 1 x BIOS FlashBack button 1 x PS/2 Keyboard/Mouse combo port BIOS: UEFI AMI BIOS, 256 Mb Flash ROM

ATX gaming motherboard with PCIe 4.0, dual M.2, 10 DrMOS power stages, Wi-Fi 6, 2.5 Gb Ethernet, HDMI, DisplayPort, SATA 6 Gbps, USB 3.2 Gen 2 Type-A and Type-C®, BIOS FlashBack™, and Aura Sync RGB lighting support AMD AM4 socket: Ready for Ryzen™ 5000 Series/ 5000 G-Series/ 4000 G-Series/ 3000 Series Desktop Processors Enhanced power solution: 8+2 DrMOS power stages, ProCool connector, military-grade TUF components, and DIGI+ VRM for maximum durability Comprehensive cooling: VRM heatsinks, PCH fanless heatsink, M.2 heatsink, hybrid fan headers and Fan Xpert 2+ utility Ultrafast connectivity: PCIe 4.0 M.2, USB 3.2 Gen 2 Type-A and Type-C® support Made for online gaming: Wi-Fi 6, Realtek 2.5Gb Ethernet, and TUF LANGuard Two-Way AI Noise Cancelation: Reduces background noise from the microphone and audio output for crystal-clear communication in games or video conferences Chipset: B550 Rozměrový formát: microATX (24.4cm x 24.4cm) Podpora pro procesory: AMD Ryzen 5000 Series/ 5000 G-Series/ 4000 G-Series/ 3000 Series Desktop Processors Pozice na paměti: 4 x DIMM DDR4, Dual Channel Memory Architecture Podpora pro paměti: DDR4 4866(OC)/4800(OC)/4600(OC)/4466(OC)/4400(OC)/4333(OC)/4266(OC)/4200(OC)/4133(OC)/4000(OC)/3866(OC)/3733(OC)/3600(OC)/3466(OC)/3400(OC)/3333(OC)/3200/3000/2933/2800/2666/2400/2133 MHz Max.velikost operační paměti: 128 GB Podpora pro paměti typu: ECC Grafická karta: (na základě procesoru) 1 x DisplayPort 1 x HDMI port Zvuková karta: Realtek 7.1 Surround Sound High Definition Audio CODEC Síťová karta: TUF LANGuard Wi-Fi 6 (802.11 a/b/g/n/ac/ax) Bluetooth 5.2 Rozšiřující sloty: AMD Ryzen 5000 Series/ 3000 Series Desktop Processors 1 x PCIe 4.0 x16 slot (supports x16 mode) AMD Ryzen 5000 G-Series/ 4000 G-Series Desktop Processors 1 x PCIe 3.0 x16 slot (supports x16 mode) AMD B550 Chipset 1 x PCIe 3.0 x16 slot (supports x4 mode) 1 x PCIe 3.0 x1 slot RAID řadič: RAID 0, 1, 10 SATA: 4 x SATA 6Gb/s ports M.2: 2 x M.2 slots (Key M) USB: Interní: 1 x USB 3.2 Gen 1 header supports additional 2 USB 3.2 Gen 1 ports 2 x USB 2.0 headers support additional 4 USB 2.0

ports Externí: 2 x USB 3.2 Gen 2 ports (1 x Type-A + 1 x USB Type-C) 4 x USB 3.2 Gen 1 ports (4 x Type-A, one port can be switched to USB BIOS FlashBack™) 2 x USB 2.0 ports (2 x Type-A) Interní porty: Fan and Cooling related 1 x 4-pin CPU Fan header 1 x 4-pin CPU OPT Fan header 2 x 4-pin Chassis Fan headers Power related: 1 x 24-pin Main Power connector 1 x 8-pin +12V Power connector Storage related: 2 x M.2 slots (Key M) 4 x SATA 6Gb/s ports USB 1 x USB 3.2 Gen 1 header supports additional 2 USB 3.2 Gen 1 ports 2 x USB 2.0 headers support additional 4 USB 2.0 ports Miscellaneous: 1 x Addressable Gen 2 header 2 x AURA RGB headers 1 x Clear CMOS header 1 x COM Port header 1 x Front Panel Audio header (AAFP) 1 x Speaker header 1 x SPI TPM header (14-1pin) 1 x 10-1 pin System Panel header Externí porty: 2 x USB 3.2 Gen 2 ports (1 x Type-A + 1 x USB Type-C) 4 x USB 3.2 Gen 1 ports (4 x Type-A, one port can be switched to USB BIOS FlashBack) 2 x USB 2.0 ports (2 x Type-A) 1 x DisplayPort 1 x HDMI port 1 x Wi-Fi Module 1 x Realtek 2.5Gb Ethernet port 5 x Audio jacks 1 x Optical S/PDIF out port 1 x BIOS FlashBack button 1 x PS/2 Keyboard/Mouse combo port BIOS: UEFI AMI BIOS, 256 Mb Flash ROM