

# MSI PRO MP242C/ 24" zakřivený/ 1920x1080/ VA/ 1ms/ 250cd/m2/ 3000:1/ HDMI/ D-Sub/ černý

**cena vč DPH:** **3588 Kč**

**cena bez DPH:** 2965 Kč

**Kód zboží (ID):** 5359688

**PN:** PRO-MP242C

**Záruka:** 24 měsíců



MSI monitor PRO MP242C, 24" zakřivený/1920 x 1080 FHD/VA/1ms/3000:1/250cd / m2 /HDMI/D-Sub MKT Spec PRO MP242C Website Name PRO MP242C Color ID1/Black-Black Local Dimming NA Display Screen Size 23.6" (60cm) Active Display Area (mm) 521(H) x 293(V) Curvature Curve 1500R Panel Type VA Resolution 1920x1080 (FHD) Pixel pitch (mm) 0.272(H)x0.272(V) Aspect Ratio 16:09 Dynamic Refresh Rate technology FreeSync Dynamic Refresh Rate Activated Range 48~75Hz HDR (High dynamic range) N/A SDR Brightness (nits) 250 HDR Brightness (Peak nits) NA Contrast Ratio 3000:01:00 DCR (Dynamic Contrast Ratio) 100000000:1 Signal Frequency 52.8~90 KHz(H) / 48~75 Hz(V) Refresh Rate 75Hz Response Time (MPRT) 1ms(MPRT) Response Time (GTG) 5ms Response Time (Tr + Tf) 27ms View Angles 178°(H)/178°(V) NTSC (CIE1976 area percentage/overlap) 85%/75% NTSC (CIE1931 area percentage/overlap) 72%/70% sRGB (CIE1976 area percentage/overlap) 98%/95% sRGB (CIE1931 area percentage/overlap) 99%/95% Adobe RGB (CIE1976 area percentage/overlap) 83%/82% Adobe RGB (CIE1931 area percentage/overlap) 75%/73% DCI-P3 (CIE1976 area percentage/overlap) 77%/77% DCI-P3 (CIE1931 area percentage/overlap) 74%/74% Rec.709 (CIE1976 area percentage/overlap) 98%/95% Rec.709 (CIE1931 area percentage/overlap) 99%/95% Rec.2020 (CIE1976 area percentage/overlap) 56%/56% Rec.2020 (CIE1931 area percentage/overlap) 52%/52% Quantum Dot NA Surface Treatment Anti-glare Touch Screen Non-touch Display Colors 16.7M Color bit 8 bits Note\_DP NA Note\_HDMI 1920 x 1080 (Up to 75Hz) Note\_DVI N/A I/O Ports HDMI 1 HDMI version 1.4b HDMI HDCP version 1,4 DisplayPort NA DisplayPort version NA DisplayPort HDCP version NA Thunderbolt NA Thunderbolt version NA Thunderbolt HDCP version NA USB Type C (DisplayPort Alternate) NA DVI NA D-Sub 1 Line-in 1 Mic-in NA Mic-in upstream NA Headphone-out 1 Audio Combo NA USB 2.0 Type A NA USB 2.0 Type B

NA USB 2.0 Type C NA USB 3.2 Gen 1 Type A NA USB 3.2 Gen 1 Type B NA USB 3.2 Gen 1 Type C NA USB 3.2 Gen 2x2 Type C NA USB 3.2 Gen 2x2 Type A NA Card reader NA Lock type Kensington Lock Speaker 2 Webcam NA Power Country EU Territory EU Entity EU OBD Power Type External Adaptor 12V 2.5A Power Input 100~240V, 50/60Hz On-mode Power Consumption (KWh/1000h) 21 Annual Energy Consumption (KWh) NA Standby-mode Power Consumption (W) 0,5 Off-mode Power Consumption (W) 0,3 Energy Efficiency Rating F Adapter's KC safety Number NA Power Cord Type C13 QC Output NA QC Output Power NA PD Output NA PD Output Power NA Warranty Warranty 24M Design Adjustment (Tilt) -7° ~ 22° Adjustment (Swivel) NA Adjustment (Height) NA Adjustment (Pivot) NA VESA Mounting 100x100mm Frameless Design Yes Pallet pallet Q'ty (by air) pcs 42 Q'ty/20cy (by air) pcs 420 Q'ty/40cy (by air) pcs 882 Dimension (L)(by air) mm 1200 Dimension (W)(by air) mm 1000 Dimension (H)(by air) mm 1356 Net Weight (by air) kg 202 Gross Weight (by air) kg 227 pallet Q'ty (by sea) pcs 70 Q'ty/20cy (by sea) pcs 700 Q'ty/40cy (by sea) pcs 1470 Dimension (L)(by sea) mm 1200 Dimension (W)(by sea) mm 1000 Dimension (H)(by sea) mm 2168 Net Weight (by sea) kg 307 Gross Weight (by sea) kg 332 Inside Carton Dimension (WxDxH) Inside Carton Dimension (WxDxH) (mm) 600 x 140 x 400 Inside Carton Dimension (WxDxH) (inch) 23.62 x 5.51 x 15.75 Outer Carton Dimension (WxDxH) Outer Carton Dimension (WxDxH) (mm) 615 x 155 x 425 Outer Carton Dimension (WxDxH) (inch) 24.21 x 6.1 x 16.73 Product Dimension with Stand (WxDxH) Product Dimension with Stand (WxDxH) (mm) 539.8 x 203 x 414.1 Product Dimension with Stand (WxDxH) (inch) 21.25 x 7.99 x 16.3 Product Dimension without Stand (WxDxH) Product Dimension without Stand (WxDxH) (mm) 539.8 x 321.8 x 74.2 Product Dimension without Stand (WxDxH) (inch) 21.25 x 12.67 x 2.92 Stand Dimension (WxDxH) Stand Dimension (WxDxH) (mm) 203 x 203 x 145.4 Stand Dimension (WxDxH) (inch) 7.99 x 7.99 x 5.72 Weight Weight (Net kg) 2,95 Weight (Net lbs) 6,5 Weight (Gross kg) 4,39 Weight (Gross lbs) 9,68 Weight Without Stand (kg) 2,57 Weight Without Stand (lbs) 5,67 Accessories DisplayPort Cable 0 HDMI Cable 1 DVI Cable 0 USB Type A to Type B Cable 0 USB Type C to Type A Cable 0 USB Type C to Type C Cable 0 Thunderbolt Cable 0 VGA Cable 0 3.5mm audio Cable 0 3.5mm combo audio Cable 0 3.5mm Mic Cable Power Cord 1 AC Adaptor 1 Quick Guide 1

MSI monitor PRO MP242C, 24" zakřivený/1920 x 1080 FHD/VA/1ms/3000:1/250cd / m2 /HDMI/D-Sub MKT Spec PRO MP242C Website Name PRO MP242C Color ID1/Black-Black Local Dimming NA Display Screen Size 23.6" (60cm) Active Display Area (mm) 521(H) x 293(V) Curvature Curve 1500R Panel Type VA Resolution 1920x1080 (FHD) Pixel pitch (mm) 0.272(H)x0.272(V) Aspect Ratio 16:09 Dynamic Refresh Rate technology FreeSync Dynamic Refresh Rate Activated Range 48~75Hz HDR (High dynamic range) N/A SDR Brightness (nits) 250 HDR Brightness (Peak nits) NA Contrast Ratio 3000:01:00 DCR (Dynamic Contrast Ratio) 100000000:1 Signal Frequency 52.8~90 KHz(H) / 48~75 Hz(V) Refresh Rate 75Hz Response Time (MPRT) 1ms(MPRT) Response Time (GTG) 5ms Response Time (Tr + Tf) 27ms View Angles 178°(H)/178°(V) NTSC (CIE1976 area percentage/overlap) 85%/75% NTSC (CIE1931 area percentage/overlap) 72%/70% sRGB (CIE1976 area

percentage/overlap) 98%/95% sRGB (CIE1931 area percentage/overlap) 99%/95% Adobe RGB (CIE1976 area percentage/overlap) 83%/82% Adobe RGB (CIE1931 area percentage/overlap) 75%/73% DCI-P3 (CIE1976 area percentage/overlap) 77%/77% DCI-P3 (CIE1931 area percentage/overlap) 74%/74% Rec.709 (CIE1976 area percentage/overlap) 98%/95% Rec.709 (CIE1931 area percentage/overlap) 99%/95% Rec.2020 (CIE1976 area percentage/overlap) 56%/56% Rec.2020 (CIE1931 area percentage/overlap) 52%/52% Quantum Dot NA Surface Treatment Anti-glare Touch Screen Non-touch Display Colors 16.7M Color bit 8 bits Note\_DP NA Note\_HDMI 1920 x 1080 (Up to 75Hz) Note\_DVI N/A I/O Ports HDMI 1 HDMI version 1.4b HDMI HDCP version 1,4 DisplayPort NA DisplayPort version NA DisplayPort HDCP version NA Thunderbolt NA Thunderbolt version NA Thunderbolt HDCP version NA USB Type C (DisplayPort Alternate) NA DVI NA D-Sub 1 Line-in 1 Mic-in NA Mic-in upstream NA Headphone-out 1 Audio Combo NA USB 2.0 Type A NA USB 2.0 Type B NA USB 2.0 Type C NA USB 3.2 Gen 1 Type A NA USB 3.2 Gen 1 Type B NA USB 3.2 Gen 1 Type C NA USB 3.2 Gen 2x2 Type C NA USB 3.2 Gen 2x2 Type A NA Card reader NA Lock type Kensington Lock Speaker 2 Webcam NA Power Country EU Territory EU Entity EU OBD Power Type External Adaptor 12V 2.5A Power Input 100~240V, 50/60Hz On-mode Power Consumption (KWh/1000h) 21 Annual Energy Consumption (KWh) NA Standby-mode Power Consumption (W) 0,5 Off-mode Power Consumption (W) 0,3 Energy Efficiency Rating F Adapter's KC safety Number NA Power Cord Type C13 QC Output NA QC Output Power NA PD Output NA PD Output Power NA Warranty Warranty 24M Design Adjustment (Tilt) -7° ~ 22° Adjustment (Swivel) NA Adjustment (Height) NA Adjustment (Pivot) NA VESA Mounting 100x100mm Frameless Design Yes Pallet pallet Q'ty (by air) pcs 42 Q'ty/20cy (by air) pcs 420 Q'ty/40cy (by air) pcs 882 Dimension (L)(by air) mm 1200 Dimension (W)(by air) mm 1000 Dimension (H)(by air) mm 1356 Net Weight (by air) kg 202 Gross Weight (by air) kg 227 pallet Q'ty (by sea) pcs 70 Q'ty/20cy (by sea) pcs 700 Q'ty/40cy (by sea) pcs 1470 Dimension (L)(by sea) mm 1200 Dimension (W)(by sea) mm 1000 Dimension (H)(by sea) mm 2168 Net Weight (by sea) kg 307 Gross Weight (by sea) kg 332 Inside Carton Dimension (WxDxH) Inside Carton Dimension (WxDxH) (mm) 600 x 140 x 400 Inside Carton Dimension (WxDxH) (inch) 23.62 x 5.51 x 15.75 Outer Carton Dimension (WxDxH) Outer Carton Dimension (WxDxH) (mm) 615 x 155 x 425 Outer Carton Dimension (WxDxH) (inch) 24.21 x 6.1 x 16.73 Product Dimension with Stand (WxDxH) Product Dimension with Stand (WxDxH) (mm) 539.8 x 203 x 414.1 Product Dimension with Stand (WxDxH) (inch) 21.25 x 7.99 x 16.3 Product Dimension without Stand (WxDxH) Product Dimension without Stand (WxDxH) (mm) 539.8 x 321.8 x 74.2 Product Dimension without Stand (WxDxH) (inch) 21.25 x 12.67 x 2.92 Stand Dimension (WxDxH) Stand Dimension (WxDxH) (mm) 203 x 203 x 145.4 Stand Dimension (WxDxH) (inch) 7.99 x 7.99 x 5.72 Weight Weight (Net kg) 2,95 Weight (Net lbs) 6,5 Weight (Gross kg) 4,39 Weight (Gross lbs) 9,68 Weight Without Stand (kg) 2,57 Weight Without Stand (lbs) 5,67 Accessories DisplayPort Cable 0 HDMI Cable 1 DVI Cable 0 USB Type A to Type B Cable 0 USB Type C to Type A Cable 0 USB Type C to Type C Cable 0 Thunderbolt Cable 0 VGA Cable 0 3.5mm audio Cable 0 3.5mm combo audio Cable 0 3.5mm Mic Cable Power Cord 1 AC Adaptor 1 Quick Guide 1