

# GIGABYTE X670E AORUS XTREME

**cena vč DPH: 19587 Kč**

cena bez DPH: 16188 Kč

**Kód zboží (ID): 5500711**

**PN: X670E-AORUS-XTREME**

**Záruka: 36 měsíců**



Chipset: AMD X670 Rozměrový formát: E-ATX Form Factor; (30.5cm x 26.9cm)  
Podpora pro procesory: AMD Ryzen 7000 Series Processors Patice procesoru: AM5  
Pozice na paměti: 4 x DDR5 DIMM, Dual channel memory architecture Podpora pro paměti: DDR5 6666(OC) / 6600(OC) / 6400(OC) / 6200(OC) / 6000(OC) / 5600(OC) / 5200 / 4800 / 4400 MT/s Max.velikost operační paměti: 128 GB (32 GB single DIMM capacity) Podpora pro paměti typu: non-ECC, XMP Grafické výstupy: (na základě procesoru) \*1 x HDMI 2.1 port, maximální rozlišení 4096x2160@60 Hz \*1 x DisplayPort 1.4, maximální rozlišení 3840x2160@144 Hz Zvuková karta: Realtek ALC1220-VB CODEC \*2/4/5.1-channel \*Podpora S/PDIF Out Síťová karta: \*Marvell AQtion AQC113C 10GbE LAN chip (10 Gbps/5 Gbps/2.5 Gbps/1 Gbps/100 Mbps) \*Intel Wi-Fi 6E AX210 a, b, g, n, ac, ax \*Bluetooth 5.3 Rozšiřující sloty: \*1 x PCI Express x16 slot, supporting PCIe 5.0 and running at x16 (PCIEX16) \*1 x PCI Express x16 slot, supporting PCIe 4.0 and running at x4 (PCIEX4) \*1 x PCI Express x16 slot, supporting PCIe 3.0 and running at x2 (PCIEX2) RAID řadič: RAID 0, RAID 1, and RAID 10 SATA: 6 x SATA 6Gb/s connectors M.2: 4 x M.2 connector USB: \*Interní: \*1 x USB Type-C header, with USB 3.2 Gen 2x2 support \*2 x USB 3.2 Gen 1 headers \*2 x USB 2.0/1.1 headers \*Externí: \*1 x USB Type-C port, with USB 3.2 Gen 2x2 support \*1 x USB Type-C port, with USB 3.2 Gen 2 support \*6 x USB 3.2 Gen 2 Type-A ports (red) \*4 x USB 2.0/1.1 ports Interní porty: \*1 x 24-pin ATX main power connector \*2 x 8-pin ATX 12V power connectors \*1 x CPU fan header \*1 x water cooling CPU fan header \*4 x system fan headers \*4 x system fan/water cooling pump headers \*2 x addressable LED strip headers \*2 x RGB LED strip headers \*1 x CPU cooler LED strip/RGB LED strip header \*4 x M.2 Socket 3 connectors \*6 x SATA 6Gb/s connectors \*1 x front panel header \*1 x front panel audio header \*1 x USB Type-C header, with USB 3.2 Gen 2x2 support \*2 x USB 3.2 Gen 1 headers \*2 x USB 2.0/1.1 headers \*1 x noise detection header \*1 x THB\_U4 add-in card connector \*1 x Trusted Platform Module header (For the GC-TPM2.0 SPI/GC-TPM2.0 SPI 2.0 module only) \*1 x power button \*1 x reset button \*2 x temperature sensor headers \*1 x

reset jumper \*1 x Clear CMOS jumper Externí porty: \*1 x Q-Flash Plus button \*1 x Clear CMOS button \*2 x SMA antenna connectors (2T2R) \*1 x DisplayPort \*1 x HDMI port \*1 x USB Type-C port, with USB 3.2 Gen 2x2 support \*1 x USB Type-C port, with USB 3.2 Gen 2 support \*6 x USB 3.2 Gen 2 Type-A ports (red) \*4 x USB 2.0/1.1 ports \*1 x RJ-45 port \*1 x optical S/PDIF Out connector \*2 x audio jacks BIOS: AMI UEFI BIOS, 1 x 256 Mbit flash Stránka výrobce:  
<http://www.gigabyte.com/Motherboard/X670E-AORUS-XTREME-rev-10#kf>

**Chipset:** AMD X670 **Rozměrový formát:** E-ATX Form Factor; (30.5cm x 26.9cm) **Podpora pro procesory:** AMD Ryzen 7000 Series Processors **Patice procesoru:** AM5 **Pozice na paměti:** 4 x DDR5 DIMM, Dual channel memory architecture **Podpora pro paměti:** DDR5 6666(OC) / 6600(OC) / 6400(OC) / 6200(OC) / 6000(OC) / 5600(OC) / 5200 / 4800 / 4400 MT/s **Max.velikost operační paměti:** 128 GB (32 GB single DIMM capacity) **Podpora pro paměti typu:** non-ECC, XMP **Grafické výstupy:** (na základě procesoru) \*1 x HDMI 2.1 port, maximální rozlišení 4096x2160@60 Hz \*1 x DisplayPort 1.4, maximální rozlišení 3840x2160@144 Hz **Zvuková karta:** Realtek ALC1220-VB CODEC \*2/4/5.1-channel \*Podpora S/PDIF Out **Síťová karta:** \*Marvell AQtion AQC113C 10GbE LAN chip (10 Gbps/5 Gbps/2.5 Gbps/1 Gbps/100 Mbps) \*Intel Wi-Fi 6E AX210 a, b, g, n, ac, ax \*Bluetooth 5.3 **Rozšiřující sloty:** \*1 x PCI Express x16 slot, supporting PCIe 5.0 and running at x16 (PCIEX16) \*1 x PCI Express x16 slot, supporting PCIe 4.0 and running at x4 (PCIEX4) \*1 x PCI Express x16 slot, supporting PCIe 3.0 and running at x2 (PCIEX2) **RAID řadič:** RAID 0, RAID 1, and RAID 10 **SATA:** 6 x SATA 6Gb/s connectors **M.2:** 4 x M.2 connector **USB:** \***Interní:** \*1 x USB Type-C header, with USB 3.2 Gen 2x2 support \*2 x USB 3.2 Gen 1 headers \*2 x USB 2.0/1.1 headers \***Externí:** \*1 x USB Type-C port, with USB 3.2 Gen 2x2 support \*1 x USB Type-C port, with USB 3.2 Gen 2 support \*6 x USB 3.2 Gen 2 Type-A ports (red) \*4 x USB 2.0/1.1 ports **Interní porty:** \*1 x 24-pin ATX main power connector \*2 x 8-pin ATX 12V power connectors \*1 x CPU fan header \*1 x water cooling CPU fan header \*4 x system fan headers \*4 x system fan/water cooling pump headers \*2 x addressable LED strip headers \*2 x RGB LED strip headers \*1 x CPU cooler LED strip/RGB LED strip header \*4 x M.2 Socket 3 connectors \*6 x SATA 6Gb/s connectors \*1 x front panel header \*1 x front panel audio header \*1 x USB Type-C header, with USB 3.2 Gen 2x2 support \*2 x USB 3.2 Gen 1 headers \*2 x USB 2.0/1.1 headers \*1 x noise detection header \*1 x THB\_U4 add-in card connector \*1 x Trusted Platform Module header (For the GC-TPM2.0 SPI/GC-TPM2.0 SPI 2.0 module only) \*1 x power button \*1 x reset button \*2 x temperature sensor headers \*1 x reset jumper \*1 x Clear CMOS jumper **Externí porty:** \*1 x Q-Flash Plus button \*1 x Clear CMOS button \*2 x SMA antenna connectors (2T2R) \*1 x DisplayPort \*1 x HDMI port \*1 x USB Type-C port, with USB 3.2 Gen 2x2 support \*1 x USB Type-C port, with USB 3.2 Gen 2 support \*6 x USB 3.2 Gen 2 Type-A ports (red) \*4 x USB 2.0/1.1 ports \*1 x RJ-45 port \*1 x optical S/PDIF Out connector \*2 x audio jacks **BIOS:** AMI UEFI BIOS, 1 x 256 Mbit flash **Stránka výrobce:**

<http://www.gigabyte.com/Motherboard/X670E-AORUS-XTREME-rev-10#kf>