

BENQ 27" LED PD2705UA/ 3840x2160/ IPS panel/ 1200:1/ 5ms/ HDMI/ DP/ 2x USB-C/ 3x USB/ repro/ Pivot/ černý

cena vč DPH: 13129 Kč

cena bez DPH: 10851 Kč

Kód zboží (ID): 5517879

PN: 9H-LKDLA-TPE

Záruka: 36 měsíců



Display Screen Size 27 inch Panel Type IPS Backlight Technology LED backlight Resolution (max.) 3840x2160 Brightness (typ.) 250 nits Brightness (peak)(HDR) 350 nits HDR HDR10 Native Contrast 1200:1 Viewing Angle (L/R) (CR>=10) 178°/178° Response Times (GtG) 5 ms Refresh Rate (Hz) 60 Color Gamut 99% Rec.709, 99% sRGB Color Mode Animation, CAD/CAM, Darkroom, DICOM, HDR, Low Blue Light, M-Book, Rec.709, sRGB, User Aspect Ratio 16:9 Display Colors 1.07 billion colors PPI 163 Display Screen Coating Anti-Glare Color Temperature 5000K, 6500K, 9300K, User Define Gamma 1.8 - 2.6, sRGB HDCP 2.2 OSD Language Arabic, Chinese (simplified), Chinese (traditional), Czech, Deutsch, English, French, Hungarian, Italian, Japanese, Korean, Netherlands, Polish, Portuguese, Romanian, Russian, Spanish, Swedish AMA Yes Audio Built-in Speaker 2.5Wx2 Headphone Jack Yes Power Voltage Rating 100 - 240V Power Supply Built-in Power Consumption (normal) 27.5 W Power Consumption (max) 152 W Power Consumption (sleep mode) <0.5 W Power Delivery(USB C / Thunderbolt 3) 65 W Dimension and Weight Tilt (down/up) -5° - 30° Swivel (left/right) 275°/ 275° Pivot 90° Height Adjustment Stand 150 mm Dimensions (HxWxD) (mm) 553 - 703 x 614 x 459.4 Dimensions (HxWxD) (inch) 21.8- 27.7 x 24.2 x 18.1 Dimensions (HxWxD) (w/o Base) (inch) 14.4 x 24.2 x 3.2 Net Weight (kg) 10 Net Weight (lb) 22 Net Weight (w/o Base) (kg) 6.2 Net Weight (w/o Base) (lb) 13.7 VESA Wall Mount 100x100 mm Accessories Other Accessories Calibration Report, Hotkey Puck G2, QSG, Warranty Card Connectivity HDMI (v2.0) 1 DisplayPort (v1.4) 1 USB C(PowerDelivery 65W, DisplayPort Alt Mode, Data) 1 USB Type B (Upstream) 2 USB C (Downstream) 1 USB 3.2 (Downstream) 3 All-in-One Connection USB-C Eye Care Flicker-free Technology Yes Low Blue Light Yes Certification TUV Certificate Flicker-free, Low Blue Light Solidworks Yes calman verified Yes Pantone Validated Yes Pantone SkinTone™ Validated Yes Professional

Video Format Support Yes Factory Calibration Report Yes Delta E(avg) ?3 Animation mode Yes CAD/CAM mode Yes Darkroom mode Yes KVM Switch Yes DualView Yes Auto Pivot Yes Uniformity Technology Yes Hotkey Puck G2 Yes PIP/PBP Yes ICCsync Yes Software Display Pilot Yes Accessory Dimension and Weight Dimensions (HxWxD) (mm) 553 - 703 x 614 x 459.4 Dimensions (HxWxD) (inch) 21.8- 27.7 x 24.2 x 18.1 Net Weight (kg) 10 Net Weight (lb) 22

Display Screen Size 27 inch Panel Type IPS Backlight Technology LED backlight Resolution (max.) 3840x2160 Brightness (typ.) 250 nits Brightness (peak)(HDR) 350 nits HDR HDR10 Native Contrast 1200:1 Viewing Angle (L/R) (CR>=10) 178°/178° Response Times (GtG) 5 ms Refresh Rate (Hz) 60 Color Gamut 99% Rec.709, 99% sRGB Color Mode Animation, CAD/CAM, Darkroom, DICOM, HDR, Low Blue Light, M-Book, Rec.709, sRGB, User Aspect Ratio 16:9 Display Colors 1.07 billion colors PPI 163 Display Screen Coating Anti-Glare Color Temperature 5000K, 6500K, 9300K, User Define Gamma 1.8 - 2.6, sRGB HDCP 2.2 OSD Language Arabic, Chinese (simplified), Chinese (traditional), Czech, Deutsch, English, French, Hungarian, Italian, Japanese, Korean, Netherlands, Polish, Portuguese, Romanian, Russian, Spanish, Swedish AMA Yes Audio Built-in Speaker 2.5Wx2 Headphone Jack Yes Power Voltage Rating 100 - 240V Power Supply Built-in Power Consumption (normal) 27.5 W Power Consumption (max) 152 W Power Consumption (sleep mode) <0.5 W Power Delivery(USB C / Thunderbolt 3) 65 W Dimension and Weight Tilt (down/up) -5° - 30° Swivel (left/right) 275°/ 275° Pivot 90° Height Adjustment Stand 150 mm Dimensions (HxWxD) (mm) 553 - 703 x 614 x 459.4 Dimensions (HxWxD) (inch) 21.8- 27.7 x 24.2 x 18.1 Dimensions (HxWxD) (w/o Base) (inch) 14.4 x 24.2 x 3.2 Net Weight (kg) 10 Net Weight (lb) 22 Net Weight (w/o Base) (kg) 6.2 Net Weight (w/o Base) (lb) 13.7 VESA Wall Mount 100x100 mm Accessories Other Accessories Calibration Report, Hotkey Puck G2, QSG, Warranty Card Connectivity HDMI (v2.0) 1 DisplayPort (v1.4) 1 USB C(PowerDelivery 65W, DisplayPort Alt Mode, Data) 1 USB Type B (Upstream) 2 USB C (Downstream) 1 USB 3.2 (Downstream) 3 All-in-One Connection USB-C Eye Care Flicker-free Technology Yes Low Blue Light Yes Certification TUV Certificate Flicker-free, Low Blue Light Solidworks Yes calman verified Yes Pantone Validated Yes Pantone SkinTone™ Validated Yes Professional Video Format Support Yes Factory Calibration Report Yes Delta E(avg) ?3 Animation mode Yes CAD/CAM mode Yes Darkroom mode Yes KVM Switch Yes DualView Yes Auto Pivot Yes Uniformity Technology Yes Hotkey Puck G2 Yes PIP/PBP Yes ICCsync Yes Software Display Pilot Yes Accessory Dimension and Weight Dimensions (HxWxD) (mm) 553 - 703 x 614 x 459.4 Dimensions (HxWxD) (inch) 21.8- 27.7 x 24.2 x 18.1 Net Weight (kg) 10 Net Weight (lb) 22