

BENQ panel 65" RE6503/ dotykový interaktivní/ UHD 4K/ provoz 18/7/ HDMI/ RS232/ RJ45/ USB-C/ Android

cena vč DPH: **47620 Kč**

cena bez DPH: 39355 Kč

Kód zboží (ID): 5555137

PN: 9H-F85TC-DE1

Záruka: 36 měsíců



Panel Screen size 65" Panel type IPS Active area 1428.5 × 803.5 mm Aspect ratio 16:9 Brightness without glass (typical) 400 nits Contrast ratio (typical) 1200:1 Dynamic contrast ratio 30,000:1 Color depth 10-bit Response time 8 ms Color gamut 72% NTSC Operation hours 18 hours / 7 days Orientation Landscape Light life (typical) 50,000 hrs Glass Hardness 9H tempered Germ-resistant coating Yes Anti-glare coating Yes Touch screen Touch technology Infrared touch Touch points up to 40 Touch Output < 10 ms System CPU A55 × 4 GPU G52 MP2 Memory | Storage 4GB | 32GB OS Android 11.0 Connectivity HDMI (in | out) 3 × HDMI 2.0 | 1 × HDMI 2.0 VGA (in | out) 1 | 0 3.5 mm Line in (1) PC Audio × 1 3.5 mm Line out Earphone × 1 SPDIF (in | out) 0 | 1 (optical) USB-A 4 × 3.0 + 2 × 2.0 USB-B (for touch) 1 × 3.0 + 1 × 2.0 USB-C 1 × 3.0 (PD 65 W) Slot-in PC (OPS) 1 Ethernet LAN 10 / 100 / 1000 Mbps (Android), 10 / 100 / 1000 Mbps (OPS) × 2 Built-in peripherals Speaker 2 × 16 W Power Power AC 100-240V 50/60Hz Maximum Power Consumption (Watt) 393.7 W Standby power consumption <0.5 W Typical power consumption 82.0 W Physical Dimensions (W × H × D) 1488.3×896.6×87.5mm (58.6 × 35.3 × 3.4 inch) Shipping dimensions (W × H × D) 1628×208×1005 mm (64.1 × 8.2 × 39.6 inch) Weight (product | shipping) 36.1 kg | 46.1 kg (79.5 lbs | 101.5 lbs) Mount (screws) VESA 600 × 400 mm (4 × M8 × 25L) Environment Operating temperature 0°C ~ 40°C Storage temperature -20°C ~ 60°C Storage humidity 10% ~ 90% RH Non-Condensing Operating humidity 10% ~ 90% RH non-condensing Software Whiteboarding EZWrite 6.0 Wireless screen sharing InstaShare 2 Account management AMS Device management DMS Quick access tool Floating Tool Broadcast system X-Sign Broadcast Accessories Cables 1 × VGA (3 m | 9.8 ft), 1 × HDMI (3 m | 9.8 ft), 1 × USB-B for touch (3 m | 9.8 ft), 1 × USB-C (1.5 m | 4.9 ft) Wall Mount (with shipment) 1 Stylus 2 Remote control 1 Power cord BQP × 6

(EU/US/AU/TW/JP/UK) ; BQE&BQA × 3 (EU/UK/US) ; BQC × 1 (CN)

Panel Screen size 65" Panel type IPS Active area 1428.5 × 803.5 mm Aspect ratio 16:9 Brightness without glass (typical) 400 nits Contrast ratio (typical) 1200:1 Dynamic contrast ratio 30,000:1 Color depth 10-bit Response time 8 ms Color gamut 72% NTSC Operation hours 18 hours / 7 days Orientation Landscape Light life (typical) 50,000 hrs Glass Hardness 9H tempered Germ-resistant coating Yes Anti-glare coating Yes Touch screen Touch technology Infrared touch Touch points up to 40 Touch Output < 10 ms System CPU A55 × 4 GPU G52 MP2 Memory | Storage 4GB | 32GB OS Android 11.0 Connectivity HDMI (in | out) 3 × HDMI 2.0 | 1 × HDMI 2.0 VGA (in | out) 1 | 0 3.5 mm Line in (1) PC Audio × 1 3.5 mm Line out Earphone × 1 SPDIF (in | out) 0 | 1 (optical) USB-A 4 × 3.0 + 2 × 2.0 USB-B (for touch) 1 × 3.0 + 1 × 2.0 USB-C 1 × 3.0 (PD 65 W) Slot-in PC (OPS) 1 Ethernet LAN 10 / 100 / 1000 Mbps (Android), 10 / 100 / 1000 Mbps (OPS) × 2 Built-in peripherals Speaker 2 × 16 W Power Power AC 100-240V 50/60Hz Maximum Power Consumption (Watt) 393.7 W Standby power consumption < 0.5 W Typical power consumption 82.0 W Physical Dimensions (W x H x D) 1488.3×896.6×87.5mm (58.6 × 35.3 × 3.4 inch) Shipping dimensions (W x H x D) 1628×208×1005 mm (64.1 × 8.2 × 39.6 inch) Weight (product | shipping) 36.1 kg | 46.1 kg (79.5 lbs | 101.5 lbs) Mount (screws) VESA 600 × 400 mm (4 × M8 × 25L) Environment Operating temperature 0°C ~ 40°C Storage temperature -20°C ~ 60°C Storage humidity 10% ~ 90% RH Non-Condensing Operating humidity 10% ~ 90% RH non-condensing Software Whiteboarding EZWrite 6.0 Wireless screen sharing InstaShare 2 Account management AMS Device management DMS Quick access tool Floating Tool Broadcast system X-Sign Broadcast Accessories Cables 1 × VGA (3 m | 9.8 ft), 1 × HDMI (3 m | 9.8 ft), 1 × USB-B for touch (3 m | 9.8 ft), 1 × USB-C (1.5 m | 4.9 ft) Wall Mount (with shipment) 1 Stylus 2 Remote control 1 Power cord BQP × 6 (EU/US/AU/TW/JP/UK) ; BQE&BQA × 3 (EU/UK/US) ; BQC × 1 (CN)