

MSI B760 GAMING PLUS WIFI

cena vč DPH: **4337 Kč**

cena bez DPH: 3584 Kč

Kód zboží (ID): 5627270

PN: B760-GAMING-PLUS-WIFI

Záruka: 36 měsíců



CHIPSET INTEL B760 CPU Support Intel® Core™ 14th/ 13th/ 12th Gen Processors, Intel® Pentium® Gold and Celeron® Processors LGA 1700 MEMORY 4x DDR5, Maximum Memory Capacity 192GB Memory Support DDR5 6800+(OC)/ 6600(OC)/ 6400(OC)/ 6200(OC)/ 6000(OC)/ 5800(OC)/ 5600(JEDEC)/ 5400(JEDEC)/ 5200(JEDEC)/ 5000(JEDEC)/ 4800(JEDEC) MHz Max. overclocking frequency: • 1DPC 1R Max speed up to 6800+ MHz • 1DPC 2R Max speed up to 6400+ MHz • 2DPC 1R Max speed up to 6000+ MHz • 2DPC 2R Max speed up to 5600+ MHz Supports Intel® XMP 3.0 OC Supports Dual-Controller Dual-Channel mode Supports non-ECC, un-buffered memory ONBOARD GRAPHICS 1x HDMI™ Support HDMI™ 2.1 with HDR, maximum resolution of 4K 60Hz* 1x DisplayPort Support DP 1.4, maximum resolution of 4K 60Hz* *Available only on processors featuring integrated graphics. Graphics specifications may vary depending on the CPU installed. SLOT 5x PCI-E x16 slot PCI_E1 Gen PCIe 4.0 supports up to x16 (From CPU) PCI_E2 Gen PCIe 3.0 supports up to x1 (From Chipset) PCI_E3 Gen PCIe 4.0 supports up to x4 (From Chipset) PCI_E4 Gen PCIe 3.0 supports up to x1 (From Chipset) PCI_E5 Gen PCIe 3.0 supports up to x1 (From Chipset) STORAGE 2x M.2 M.2_1 Source (From CPU) supports up to PCIe 4.0 x4 , supports 22110/2280/2260/2242 devices M.2_2 Source (From Chipset) supports up to PCIe 4.0 x4 / SATA mode, supports 2280/2260/2242 devices 4x SATA 6G * SATA8 will be unavailable when installing M.2 SATA SSD in the M2_2 slot. RAID Supports RAID 0, RAID 1, RAID 5 and RAID 10 for SATA storage devices USB 4x USB 2.0 (Rear) 4x USB 2.0 (Front) 2x USB 3.2 Gen1 Type A (Front) 1x USB 3.2 Gen1 Type C (Front) 2x USB 3.2 Gen2 Type A (Rear) 1x USB 3.2 Gen2 Type C (Rear) LAN Realtek® RTL8125BG 2.5G LAN WIRELESS LAN & BLUETOOTH Intel® Wi-Fi 6E The Wireless module is pre-installed in the M.2 (Key-E) slot Supports MU-MIMO TX/RX, 2.4GHz / 5GHz / 6GHz* (160MHz) up to 2.4Gbps Supports 802.11 a/ b/ g/ n/ ac/ ax Supports Bluetooth® 5.3, FIPS, FISMA * Wi-Fi 6E 6GHz may depend on every country's regulations and will be ready in Windows 11. ** Bluetooth 5.3 will be ready in Windows 10 build 21H1 and Windows 11. AUDIO Realtek® ALC897

Codec 7.1-Channel High Definition Audio Supports S/PDIF output INTERNAL IO 1x Power Connector(ATX_PWR) 2x Power Connector(CPU_PWR) 1x CPU Fan 1x Pump Fan 5x System Fan 2x Front Panel (JFP) 1x Chassis Intrusion (JCI) 1x Front Audio (JAUD) 1x Printer Port (JLPT) 1x Com Port (JCOM) 1x TBT connector (JTBT, supports RTD3) 2x Addressable V2 RGB LED connector (JARGB_V2) 1x RGB LED connector(JRGB) 1x TPM pin header(Support TPM 2.0) 4x USB 2.0 ports 2x USB 3.2 Gen1 Type A ports 1x USB 3.2 Gen1 Type C ports LED FEATURE 4x EZ Debug LED BACK PANEL PORTS Keyboard / Mouse DisplayPort 2.5G LAN USB 2.0 Wi-Fi / Bluetooth Audio Connectors USB 2.0 HDMI™ USB 3.2 Gen 2 10Gbps (Type-A) USB 3.2 Gen 2 10Gbps (Type-C) S/PDIF-OUT OPERATING SYSTEM Support for Windows® 11 64-bit, Windows® 10 64-bit PCB INFO ATX 243.84mmx304.8mm

CHIPSET INTEL B760 CPU Support Intel® Core™ 14th/ 13th/ 12th Gen Processors, Intel® Pentium® Gold and Celeron® Processors LGA 1700 MEMORY 4x DDR5, Maximum Memory Capacity 192GB Memory Support DDR5 6800+(OC)/ 6600(OC)/ 6400(OC)/ 6200(OC)/ 6000(OC)/ 5800(OC)/ 5600(JEDEC)/ 5400(JEDEC)/ 5200(JEDEC)/ 5000(JEDEC)/ 4800(JEDEC) MHz Max. overclocking frequency: • 1DPC 1R Max speed up to 6800+ MHz • 1DPC 2R Max speed up to 6400+ MHz • 2DPC 1R Max speed up to 6000+ MHz • 2DPC 2R Max speed up to 5600+ MHz Supports Intel® XMP 3.0 OC Supports Dual-Controller Dual-Channel mode Supports non-ECC, un-buffered memory ONBOARD GRAPHICS 1x HDMI™ Support HDMI™ 2.1 with HDR, maximum resolution of 4K 60Hz* 1x DisplayPort Support DP 1.4, maximum resolution of 4K 60Hz* *Available only on processors featuring integrated graphics. Graphics specifications may vary depending on the CPU installed. SLOT 5x PCI-E x16 slot PCI_E1 Gen PCIe 4.0 supports up to x16 (From CPU) PCI_E2 Gen PCIe 3.0 supports up to x1 (From Chipset) PCI_E3 Gen PCIe 4.0 supports up to x4 (From Chipset) PCI_E4 Gen PCIe 3.0 supports up to x1 (From Chipset) PCI_E5 Gen PCIe 3.0 supports up to x1 (From Chipset) STORAGE 2x M.2 M.2_1 Source (From CPU) supports up to PCIe 4.0 x4 , supports 22110/2280/2260/2242 devices M.2_2 Source (From Chipset) supports up to PCIe 4.0 x4 / SATA mode, supports 2280/2260/2242 devices 4x SATA 6G * SATA8 will be unavailable when installing M.2 SATA SSD in the M2_2 slot. RAID Supports RAID 0, RAID 1, RAID 5 and RAID 10 for SATA storage devices USB 4x USB 2.0 (Rear) 4x USB 2.0 (Front) 2x USB 3.2 Gen1 Type A (Front) 1x USB 3.2 Gen1 Type C (Front) 2x USB 3.2 Gen2 Type A (Rear) 1x USB 3.2 Gen2 Type C (Rear) LAN Realtek® RTL8125BG 2.5G LAN WIRELESS LAN & BLUETOOTH Intel® Wi-Fi 6E The Wireless module is pre-installed in the M.2 (Key-E) slot Supports MU-MIMO TX/RX, 2.4GHz / 5GHz / 6GHz* (160MHz) up to 2.4Gbps Supports 802.11 a/ b/ g/ n/ ac/ ax Supports Bluetooth® 5.3, FIPS, FISMA * Wi-Fi 6E 6GHz may depend on every country's regulations and will be ready in Windows 11. ** Bluetooth 5.3 will be ready in Windows 10 build 21H1 and Windows 11. AUDIO Realtek® ALC897 Codec 7.1-Channel High Definition Audio Supports S/PDIF output INTERNAL IO 1x Power Connector(ATX_PWR) 2x Power Connector(CPU_PWR) 1x CPU Fan 1x Pump Fan 5x System Fan 2x Front Panel (JFP) 1x Chassis Intrusion (JCI) 1x Front Audio (JAUD) 1x Printer Port (JLPT) 1x Com Port (JCOM) 1x TBT connector (JTBT, supports RTD3) 2x Addressable V2 RGB LED connector (JARGB_V2) 1x RGB

LED connector(JRGB) 1x TPM pin header(Support TPM 2.0) 4x USB 2.0 ports 2x USB 3.2 Gen1 Type A ports 1x USB 3.2 Gen1 Type C ports LED FEATURE 4x EZ Debug LED BACK PANEL PORTS Keyboard / Mouse DisplayPort 2.5G LAN USB 2.0 Wi-Fi / Bluetooth Audio Connectors USB 2.0 HDMI™ USB 3.2 Gen 2 10Gbps (Type-A) USB 3.2 Gen 2 10Gbps (Type-C) S/PDIF-OUT OPERATING SYSTEM Support for Windows® 11 64-bit, Windows® 10 64-bit PCB INFO ATX 243.84mmx304.8mm