

MSI PRO B650-S WIFI / AMD B650 / AM5 / 4x DDR5 / 2x M.2 / HDMI / DP / USB-C / WiFi / ATX

cena vč DPH: **4563 Kč**

cena bez DPH: 3771 Kč

Kód zboží (ID): 5848022

PN: PRO-B650-S-WIFI

Záruka: 36 měsíců



CPU Supports AMD Ryzen™ 7000 Series Desktop Processors Socket AM5 MEMORY 4x DDR5, Maximum Memory Capacity 192GB Memory Support DDR5 7200+(OC)/ 7000(OC)/ 6800(OC)/ 6600(OC)/ 6400(OC)/ 6200(OC)/ 6000(OC)/ 5800(OC)/ 5600(OC)/ 5400(OC)/ 5200(OC)/ 5000(OC)/ 4800(JEDEC) MHz Max. overclocking frequency: • 1DPC 1R Max speed up to 7200+ MHz • 1DPC 2R Max speed up to 6000+ MHz • 2DPC 1R Max speed up to 6000+ MHz • 2DPC 2R Max speed up to 5400+ MHz Supports Dual-Channel mode Supports non-ECC, un-buffered memory Supports AMD EXPO ONBOARD GRAPHICS 1x HDMI™ Support HDMITM 2.1, maximum resolution of 4K 60Hz* 1x DisplayPort Supports DP1.4, maximum resolution of 4K 60Hz* *Available only on processors featuring integrated graphics. Graphics specifications may vary depending on the CPU installed. SLOT 2x PCI-E x16 slot 1x PCI-E x1 slot PCI_E1 Gen PCIe 4.0 supports up to x16 (From CPU) PCI_E2 Gen PCIe 3.0 supports up to x1 (From Chipset) PCI_E3 Gen PCIe 4.0 supports up to x4 (From Chipset) MULTI-GPU AMD MULTI-GPU Support STORAGE 2x M.2 M.2_1 Source (From CPU) supports up to PCIe 4.0 x4 , supports 22110/2280 devices M.2_2 Source (From CPU) supports up to PCIe 4.0 x4 , supports 2280/2260 devices 4x SATA 6G RAID Supports RAID 0 and RAID 1 for SATA storage devices* Supports RAID 0 and RAID 1 for M.2 NVMe storage devices USB 4x USB 2.0 (Front) 4x USB 3.2 Gen1 Type A (Rear) 2x USB 3.2 Gen1 Type A (Front) 3x USB 3.2 Gen2 Type A (Rear) 1x USB 3.2 Gen2 Type C (Front) 1x USB 3.2 Gen2x2 Type C (Rear) LAN Realtek® 8125BG 2.5G LAN WIRELESS LAN & BLUETOOTH AMD Wi-Fi 6E The Wireless module is pre-installed in the M.2 (Key-E) slot Supports MU-MIMO TX/RX Supports 20MHz, 40MHz, 80MHz bandwidth in 2.4GHz/ 5GHz or 6GHz* bands Supports 802.11 a/ b/ g/ n/ ac/ ax Supports Bluetooth® 5.3** * Wi-Fi 6E 6GHz may depend on every country's regulations and will be ready in Windows 11. ** Bluetooth 5.3 will be ready in

Windows 10 build 21H1 and Windows 11. AUDIO Realtek® ALC897 Codec
7.1-Channel High Definition Audio INTERNAL IO 1x Power Connector(ATX_PWR) 2x
Power Connector(CPU_PWR) 1x CPU Fan 1x Pump Fan 4x System Fan 2x Front Panel
(JFP) 1x Chassis Intrusion (JCI) 1x Front Audio (JAUD) 1x Com Port (JCOM) 1x Tuning
Controller connector(JDASH) 2x Addressable V2 RGB LED connector (JARGB_V2) 2x
RGB LED connector(JRGB) 1x TPM pin header(Support TPM 2.0) 4x USB 2.0 ports 2x
USB 3.2 Gen1 Type A ports 1x USB 3.2 Gen2 Type C ports LED FEATURE 4x EZ
Debug LED BACK PANEL PORTS DisplayPort 2.5G LAN USB 3.2 Gen 2 10Gbps (Type-
A) USB 3.2 Gen 1 5Gbps (Type-A) Wi-Fi / Bluetooth Audio connectors Flash BIOS
Button HDMI™ USB 3.2 Gen 2 10Gbps (Type-A) USB 3.2 Gen 2x2 20Gbps (Type-C)
OPERATING SYSTEM Support for Windows® 11 64-bit, Windows® 10 64-bit PCB
INFO ATX 243.84mmx304.8mm

CPU Supports AMD Ryzen™ 7000 Series Desktop Processors Socket AM5 MEMORY
4x DDR5, Maximum Memory Capacity 192GB Memory Support DDR5 7200+(OC)/
7000(OC)/ 6800(OC)/ 6600(OC)/ 6400(OC)/ 6200(OC)/ 6000(OC)/ 5800(OC)/
5600(OC)/ 5400(OC)/ 5200(OC)/ 5000(OC)/ 4800(JEDEC) MHz Max. overclocking
frequency: • 1DPC 1R Max speed up to 7200+ MHz • 1DPC 2R Max speed up to
6000+ MHz • 2DPC 1R Max speed up to 6000+ MHz • 2DPC 2R Max speed up to
5400+ MHz Supports Dual-Channel mode Supports non-ECC, un-buffered memory
Supports AMD EXPO ONBOARD GRAPHICS 1x HDMI™ Support HDMITM 2.1,
maximum resolution of 4K 60Hz* 1x DisplayPort Supports DP1.4, maximum
resolution of 4K 60Hz* *Available only on processors featuring integrated graphics.
Graphics specifications may vary depending on the CPU installed. SLOT 2x PCI-E
x16 slot 1x PCI-E x1 slot PCI_E1 Gen PCIe 4.0 supports up to x16 (From CPU) PCI_E2
Gen PCIe 3.0 supports up to x1 (From Chipset) PCI_E3 Gen PCIe 4.0 supports up to
x4 (From Chipset) MULTI-GPU AMD MULTI-GPU Support STORAGE 2x M.2 M.2_1
Source (From CPU) supports up to PCIe 4.0 x4 , supports 22110/2280 devices
M.2_2 Source (From CPU) supports up to PCIe 4.0 x4 , supports 2280/2260 devices
4x SATA 6G RAID Supports RAID 0 and RAID 1 for SATA storage devices* Supports
RAID 0 and RAID 1 for M.2 NVMe storage devices USB 4x USB 2.0 (Front) 4x USB
3.2 Gen1 Type A (Rear) 2x USB 3.2 Gen1 Type A (Front) 3x USB 3.2 Gen2 Type A
(Rear) 1x USB 3.2 Gen2 Type C (Front) 1x USB 3.2 Gen2x2 Type C (Rear) LAN
Realtek® 8125BG 2.5G LAN WIRELESS LAN & BLUETOOTH AMD Wi-Fi 6E The
Wireless module is pre-installed in the M.2 (Key-E) slot Supports MU-MIMO TX/RX
Supports 20MHz, 40MHz, 80MHz bandwidth in 2.4GHz/ 5GHz or 6GHz* bands
Supports 802.11 a/ b/ g/ n/ ac/ ax Supports Bluetooth® 5.3** * Wi-Fi 6E 6GHz may
depend on every country's regulations and will be ready in Windows 11. **
Bluetooth 5.3 will be ready in Windows 10 build 21H1 and Windows 11. AUDIO
Realtek® ALC897 Codec 7.1-Channel High Definition Audio INTERNAL IO 1x Power
Connector(ATX_PWR) 2x Power Connector(CPU_PWR) 1x CPU Fan 1x Pump Fan 4x
System Fan 2x Front Panel (JFP) 1x Chassis Intrusion (JCI) 1x Front Audio (JAUD) 1x
Com Port (JCOM) 1x Tuning Controller connector(JDASH) 2x Addressable V2 RGB
LED connector (JARGB_V2) 2x RGB LED connector(JRGB) 1x TPM pin
header(Support TPM 2.0) 4x USB 2.0 ports 2x USB 3.2 Gen1 Type A ports 1x USB

3.2 Gen2 Type C ports LED FEATURE 4x EZ Debug LED BACK PANEL PORTS
DisplayPort 2.5G LAN USB 3.2 Gen 2 10Gbps (Type-A) USB 3.2 Gen 1 5Gbps (Type-
A) Wi-Fi / Bluetooth Audio connectors Flash BIOS Button HDMI™ USB 3.2 Gen 2
10Gbps (Type-A) USB 3.2 Gen 2x2 20Gbps (Type-C) OPERATING SYSTEM Support
for Windows® 11 64-bit, Windows® 10 64-bit PCB INFO ATX 243.84mmx304.8mm