

MSI MAG B760M MORTAR WIFI II / Intel B760 / LGA1700 / 4x DDR5 / 3x M.2 / HDMI / DP / USB-C / WiFi / mATX

cena vč DPH: **5800 Kč**

cena bez DPH: 4793 Kč

Kód zboží (ID): 5888756

PN: MAG-B760M-MORTAR-WIFI-II

Záruka: 36 měsíců



CHIPSET INTEL B760 CPU Support Intel® Core™ 14th/ 13th/ 12th Gen Processors, Intel® Pentium® Gold and Celeron® Processors LGA1700 MEMORY 4x DDR5, Maximum Memory Capacity 192GB Memory Support 7800+(OC)/ 7600(OC)/ 7400(OC)/ 7200(OC)/ 7000(OC)/ 6800(OC)/ 6600(OC)/ 6400(OC)/ 6200(OC)/ 6000(OC)/ 5800(OC)/ 5600(JEDEC)/ 5400(JEDEC)/ 5200(JEDEC)/ 5000(JEDEC)/ 4800(JEDEC) MHz Max. overclocking frequency: • 1DPC 1R Max speed up to 7800+ MHz • 1DPC 2R Max speed up to 6600+ MHz • 2DPC 1R Max speed up to 6400+ MHz • 2DPC 2R Max speed up to 5600+ MHz Supports Dual-Channel mode Supports non-ECC, un-buffered memory Supports Intel® Extreme Memory Profile ONBOARD GRAPHICS 1x HDMI™ Support HDMI™ 2.1 with HDR, maximum resolution of 4K 60Hz* 1x DisplayPort Support DP 1.4, maximum resolution of 4K 60Hz* *Available only on processors featuring integrated graphics. Graphics specifications may vary depending on the CPU installed. SLOT 1x PCI-E x16 slot Supports x16/x4 PCI_E1 Gen PCIe 5.0 supports up to x16 (From CPU) PCI_E2 Gen PCIe 3.0 supports up to x4 (From Chipset) STORAGE 3x M.2 M.2_1 Source (From CPU) supports up to PCIe 4.0 x4 , supports 2280/2260/2242 devices M.2_2 Source (From Chipset) supports up to PCIe 4.0 x4 , supports 2280/2260 devices M.2_3 Source (From Chipset) supports up to PCIe 4.0 x4 / SATA mode, supports 2280 devices 4x SATA 6G RAID Supports RAID 0, RAID 1, RAID 5 and RAID 10 for SATA storage devices USB 4x USB 2.0 (Rear) 4x USB 2.0 (Front) 2x USB 3.2 Gen1 Type A (Front) 3x USB 3.2 Gen2 Type A (Rear) 1x USB 3.2 Gen2 Type C (Front) 1x USB 3.2 Gen2x2 Type C (Rear) LAN Realtek® 2.5Gbps LAN WIRELESS LAN & BLUETOOTH Intel® Wi-Fi 6E The Wireless module is pre-installed in the M.2 (Key-E) slot Supports MU-MIMO TX/RX, 2.4GHz / 5GHz / 6GHz* (160MHz) up to 2.4Gbps Supports 802.11 a/ b/ g/ n/ ac/ ax Supports Bluetooth® 5.3, FIPS, FISMA * Wi-Fi 6E 6GHz may depend on every country's

regulations and will be ready in Windows 11. ** Bluetooth 5.3 will be ready in Windows 10 build 21H1 and Windows 11. AUDIO Realtek® ALC897 Codec 7.1-Channel High Definition Audio Supports S/PDIF output INTERNAL IO 1x Power Connector(ATX_PWR) 2x Power Connector(CPU_PWR) 1x CPU Fan 1x Pump Fan 4x System Fan 2x Front Panel (JFP) 1x Chassis Intrusion (JCI) 1x Front Audio (JAUD) 1x Tuning Controller connector(JDASH) 2x Addressable V2 RGB LED connector (JARGB_V2) 1x RGB LED connector(JRGB) 1x TPM pin header(Support TPM 2.0) 4x USB 2.0 ports 2x USB 3.2 Gen1 Type A ports 1x USB 3.2 Gen2 Type C ports 1x USB4 card connector (JTBT_U4_1, supports RTD3) LED FEATURE 4x EZ Debug LED BACK PANEL PORTS DisplayPort 1.4 USB 3.2 Gen 2 10Gbps Type-A 2.5G LAN Port Wi-Fi / Bluetooth HD Audio Connectors USB 2.0 HDMI™ 2.1 Port USB 3.2 Gen 2x2 20Gbps Type-C USB 3.2 Gen 2 10Gbps Type-A OPERATING SYSTEM Support for Windows® 11 64-bit, Windows® 10 64-bit PCB INFO mATX 243.84mmx243.84mm

CHIPSET INTEL B760 CPU Support Intel® Core™ 14th/ 13th/ 12th Gen Processors, Intel® Pentium® Gold and Celeron® Processors LGA1700 MEMORY 4x DDR5, Maximum Memory Capacity 192GB Memory Support 7800+(OC)/ 7600(OC)/ 7400(OC)/ 7200(OC)/ 7000(OC)/ 6800(OC)/ 6600(OC)/ 6400(OC)/ 6200(OC)/ 6000(OC)/ 5800(OC)/ 5600(JEDEC)/ 5400(JEDEC)/ 5200(JEDEC)/ 5000(JEDEC)/ 4800(JEDEC) MHz Max. overclocking frequency: • 1DPC 1R Max speed up to 7800+ MHz • 1DPC 2R Max speed up to 6600+ MHz • 2DPC 1R Max speed up to 6400+ MHz • 2DPC 2R Max speed up to 5600+ MHz Supports Dual-Channel mode Supports non-ECC, un-buffered memory Supports Intel® Extreme Memory Profile ONBOARD GRAPHICS 1x HDMI™ Support HDMITM 2.1 with HDR, maximum resolution of 4K 60Hz* 1x DisplayPort Support DP 1.4, maximum resolution of 4K 60Hz* *Available only on processors featuring integrated graphics. Graphics specifications may vary depending on the CPU installed. SLOT 1x PCI-E x16 slot Supports x16/x4 PCI_E1 Gen PCIe 5.0 supports up to x16 (From CPU) PCI_E2 Gen PCIe 3.0 supports up to x4 (From Chipset) STORAGE 3x M.2 M.2_1 Source (From CPU) supports up to PCIe 4.0 x4 , supports 2280/2260/2242 devices M.2_2 Source (From Chipset) supports up to PCIe 4.0 x4 , supports 2280/2260 devices M.2_3 Source (From Chipset) supports up to PCIe 4.0 x4 / SATA mode, supports 2280 devices 4x SATA 6G RAID Supports RAID 0, RAID 1, RAID 5 and RAID 10 for SATA storage devices USB 4x USB 2.0 (Rear) 4x USB 2.0 (Front) 2x USB 3.2 Gen1 Type A (Front) 3x USB 3.2 Gen2 Type A (Rear) 1x USB 3.2 Gen2 Type C (Front) 1x USB 3.2 Gen2x2 Type C (Rear) LAN Realtek® 2.5Gbps LAN WIRELESS LAN & BLUETOOTH Intel® Wi-Fi 6E The Wireless module is pre-installed in the M.2 (Key-E) slot Supports MU-MIMO TX/RX, 2.4GHz / 5GHz / 6GHz* (160MHz) up to 2.4Gbps Supports 802.11 a/ b/ g/ n/ ac/ ax Supports Bluetooth® 5.3, FIPS, FISMA * Wi-Fi 6E 6GHz may depend on every country's regulations and will be ready in Windows 11. ** Bluetooth 5.3 will be ready in Windows 10 build 21H1 and Windows 11. AUDIO Realtek® ALC897 Codec 7.1-Channel High Definition Audio Supports S/PDIF output INTERNAL IO 1x Power Connector(ATX_PWR) 2x Power Connector(CPU_PWR) 1x CPU Fan 1x Pump Fan 4x System Fan 2x Front Panel (JFP) 1x Chassis Intrusion (JCI) 1x Front Audio (JAUD) 1x Tuning Controller connector(JDASH) 2x Addressable V2

RGB LED connector (JARGB_V2) 1x RGB LED connector(JRGB) 1x TPM pin header(Support TPM 2.0) 4x USB 2.0 ports 2x USB 3.2 Gen1 Type A ports 1x USB 3.2 Gen2 Type C ports 1x USB4 card connector (JTBT_U4_1, supports RTD3) LED FEATURE 4x EZ Debug LED BACK PANEL PORTS DisplayPort 1.4 USB 3.2 Gen 2 10Gbps Type-A 2.5G LAN Port Wi-Fi / Bluetooth HD Audio Connectors USB 2.0 HDMI™ 2.1 Port USB 3.2 Gen 2x2 20Gbps Type-C USB 3.2 Gen 2 10Gbps Type-A OPERATING SYSTEM Support for Windows® 11 64-bit, Windows® 10 64-bit PCB INFO mATX 243.84mmx243.84mm