

BenQ LCD RE6503A 65" 3840x2160 touch IPS/1200:1/3xHDMI/VGA/USB-C/LAN/repro 2x20W/Android 11

cena vč DPH: **44408 Kč**

cena bez DPH: 36700 Kč

Kód zboží (ID): 5897231

PN: 9H-F9STB-DE1

Záruka: 36 měsíců



Panel Screen size 65" Panel type IPS Resolution UHD 3840 × 2160 pixels Active area 1428.5 × 803.5 mm Aspect ratio 16:09 Brightness without glass (typical) 450 nits Contrast ratio (typical) 1200:01:00 Dynamic contrast ratio 30,000:1 Color depth 8-bit Response time 8 ms Color gamut 72% NTSC Operation hours 18 hours / 7 days Orientation Landscape Light life (typical) 50,000 hrs Glass Hardness 9H tempered Germ-resistant coating Availability dependent on region Anti-glare coating Yes Touch screen Touch technology Infrared touch Touch points up to 40 Response time < 10 ms System CPU A55 × 4 GPU G52 2EE MC1 Memory | Storage 4GB | 32GB OS Android 11.0 Connectivity HDMI (in | out) 3 × HDMI 2.0 | No DisplayPort (in | out) 1 × 1.2 | No VGA (in | out) 1 | 0 3.5 mm Line in (1) PC Audio × 1 3.5 mm Line out Earphone × 1 SPDIF (in | out) 0 | 1 (optical) USB-A 1 × 2.0 + 3 × 3.0 USB-B (for touch) 2 × 2.0 USB-C 1 × 2.0 Slot-in PC (OPS) 1 Ethernet LAN 10 / 100 / 1000 Mbps (Android), 10 / 100 / 1000 Mbps (OPS) × 2 Built-in peripherals Speaker 2 × 20 W (max) Power Power AC 100-240V 50/60Hz Standby power consumption <0.5 W Typical power consumption 124 W Physical Dimensions (W × H × D) 1484.5 × 908.1 × 90 mm (58.4 × 35.8 × 3.5 inch) Shipping dimensions (W × H × D) 1665 × 1040 × 225 mm (65.5 × 40.9 × 8.9 inch) Weight (product | shipping) 38.6 kg | 51.9kg (85.1 lbs | 114.4 lbs) Mount (screws) VESA 500 × 400 mm (4 × M8 × 25L) Environment Operating temperature 0°C ~ 40°C | 32°F ~ 104°F Storage temperature -10°C ~ 60°C | 14°F ~ 140°F Storage humidity 10% ~ 90% RH Non-Condensing Operating humidity 20% ~ 85% RH non-condensing Software Whiteboarding EZWrite 6.0 Wireless screen sharing InstaShare 2 Account management AMS Device management DMS Quick access tool Floating Tool Broadcast system X-Sign Broadcast Accessories Cables 1 × VGA (3 m | 9.8 ft), 1 × HDMI (3 m | 9.8 ft), 1 × USB-B for touch (3 m | 9.8 ft), 1 × USB-C (1.5 m | 4.9 ft) Wall Mount (with shipment)

1 Stylus 2 Remote control 1 Power cord BQE: × 2 (EU/UK) ; BQP: × 5 (EU/UK/US/AU/JP) ; BQAU: × 2 (AU/JP) ; BQin: × 1 (IN) ; BQA: × 1 (US) ; BQC: × 1 (CN)

Panel Screen size 65" Panel type IPS Resolution UHD 3840 × 2160 pixels Active area 1428.5 × 803.5 mm Aspect ratio 16:09 Brightness without glass (typical) 450 nits Contrast ratio (typical) 1200:01:00 Dynamic contrast ratio 30,000:1 Color depth 8-bit Response time 8 ms Color gamut 72% NTSC Operation hours 18 hours / 7 days Orientation Landscape Light life (typical) 50,000 hrs Glass Hardness 9H tempered Germ-resistant coating Availability dependent on region Anti-glare coating Yes Touch screen Touch technology Infrared touch Touch points up to 40 Response time < 10 ms System CPU A55 × 4 GPU G52 2EE MC1 Memory | Storage 4GB | 32GB OS Android 11.0 Connectivity HDMI (in | out) 3 × HDMI 2.0 | No DisplayPort (in | out) 1 × 1.2 | No VGA (in | out) 1 | 0 3.5 mm Line in (1) PC Audio × 1 3.5 mm Line out Earphone × 1 SPDIF (in | out) 0 | 1 (optical) USB-A 1 × 2.0 + 3 × 3.0 USB-B (for touch) 2 × 2.0 USB-C 1 × 2.0 Slot-in PC (OPS) 1 Ethernet LAN 10 / 100 / 1000 Mbps (Android), 10 / 100 / 1000 Mbps (OPS) × 2 Built-in peripherals Speaker 2 × 20 W (max) Power Power AC 100-240V 50/60Hz Standby power consumption < 0.5 W Typical power consumption 124 W Physical Dimensions (W × H × D) 1484.5 × 908.1 × 90 mm (58.4 × 35.8 × 3.5 inch) Shipping dimensions (W × H × D) 1665 × 1040 × 225 mm (65.5 × 40.9 × 8.9 inch) Weight (product | shipping) 38.6 kg | 51.9kg (85.1 lbs | 114.4 lbs) Mount (screws) VESA 500 × 400 mm (4 × M8 × 25L) Environment Operating temperature 0°C ~ 40°C | 32°F ~ 104°F Storage temperature -10°C ~ 60°C | 14°F ~ 140°F Storage humidity 10% ~ 90% RH Non-Condensing Operating humidity 20% ~ 85% RH non-condensing Software Whiteboarding EZWrite 6.0 Wireless screen sharing InstaShare 2 Account management AMS Device management DMS Quick access tool Floating Tool Broadcast system X-Sign Broadcast Accessories Cables 1 × VGA (3 m | 9.8 ft), 1 × HDMI (3 m | 9.8 ft), 1 × USB-B for touch (3 m | 9.8 ft), 1 × USB-C (1.5 m | 4.9 ft) Wall Mount (with shipment) 1 Stylus 2 Remote control 1 Power cord BQE: × 2 (EU/UK) ; BQP: × 5 (EU/UK/US/AU/JP) ; BQAU: × 2 (AU/JP) ; BQin: × 1 (IN) ; BQA: × 1 (US) ; BQC: × 1 (CN)