

BenQ LU9245 WUXGA/ DLP projektor/ Laser/ 7000ANSI/ 3M:1/ 2x VGA/ 2x HDMI/ DVI-D/ USB/ LAN/ repro

cena vč DPH: 245386 Kč

cena bez DPH: 202798 Kč

Kód zboží (ID): 6170630

PN: 9H-JKY77-26E

Záruka: 36 měsíců



Projektor neobsahuje objektiv Optical Throw Ratio LS2ST3 Wide Fix: 0.778 LS2ST1 Wide Zoom: 1.1 ~ 1.3 LS2SD2 Standard: 1.54 ~ 1.93 LS2LT1 Semi Long: 1.93 ~ 2.9 LS2LT2 Long Zoom: 3 ~ 5 LS2ST2 Short Throw: 0.77~1.1 LS2ST4 Semi Throw: 1.25~1.6 Zoom Ratio LS2ST3 Wide Fix: Fixed LS2ST1 Wide Zoom: 1.18x LS2ST2 Short Throw: 1.42x LS2ST4 Semi Throw: 1.28x LS2SD2 Standard: 1.25x LS2LT1 Semi Long: 1.5x LS2LT2 Long Zoom: 1.67x Lens Shift Vertical: -15% ~ 55% Horizontal: -5%~5%, Standard Lens Keystone Correction Vertical: ± 30 degrees Horizontal: ± 30 degrees Projection Size 50" ~ 500" , Standard Lens Projection Offset N/A Display Projection System DLP Single 0.67" WUXGA DMD type DC3 DMD Chip Brightness 7000 ANSI Lumens Contrast Ratio* 3,000,000:1 Display Color 1.07 Billion Colors Aspect Ratio Native 16:10 (6 aspect ratio selectable) Light Source Laser diodes Light Source Life* 20,000/38,000/70,000 hours(Normal/Eco/Dimming) Native Resolution 1920x1200 pixels Audio Built-in Speaker 20W (10Wx2) Feature Security Security Bar,Kensington anti-theft lock slot Feature Rec.709 96% Blank to True Black 4K Compatible DICOM Simulation Mode, 360 Degree and Portrait Projection,Corner fit Custom Lightsource Mode (light power adjustment) Dust Proof Engine 24/7 Hours Operating Blanking Dynamic Dimming Compatibility Resolution Support VGA (640 x 480) to WUXGA (1920 x 1200) Horizontal Frequency 15~102 KHz Vertical Scan Rate 23 ~ 120 Hz HDTV Compatibility 480i, 480p, 576i, 567p, 720p, 1080i, 1080p Video Compatibility NTSC, PAL, SECAM Power Power Consumption (Max/Normal/Eco) 650W/600W/400W Standby Power Consumption Normal < 0.5Watts. Network < 2W. Dimension and Weight Product Dimensions (WxHxD) 525x216 x470 mm (with feet) Product Weight 24 kg (without lens) Operation Condition Operating Temperature 0 ~ 40 °C Noise Level (Normal/Eco) 36/34dBA Accessories Accessories (Standard) Installation Guide Safety Guide

Remote Control AA Battery x2 VGA cable(1.8m) Power Cord 3pin VESA to BNC Cable
Warranty card (by Region) Accessories (Optional) Instashow WDC10 Ceiling Mount
(CMG6) LS2ST3 Wide Fix (5J.JDH37.002) LS2ST1 Wide Zoom (5J.JDH37.011) LS2ST2
Short Throw(5A.JK337.001) LS2ST4 Semi Throw(5A.JK337.011) LS2SD2 Standard
(5J.JEN37.001) LS2LT1 Semi Long (5J.JDH37.032) LS2LT2 Long Zoom (5J.JDH37.041)
OSD On Screen Display Language Arabic/Bulgarian/ Croatian/ Czech/ Danish/ Dutch/
English/ Finnish/ French/ German/ Greek/ Hindi/ Hungarian/ Italian/ Indonesian/
Japanese/ Korean/ Norwegian/ Polish/ Portuguese/ Romanian/ Russian/ Simplified
Chinese/Spanish/ Swedish/ Turkish/ Thai/ Traditional Chinese (28 Languages)
InstaShow Host Power Supply 100 ~ 240V AC

Projektor neobsahuje objektiv Optical Throw Ratio LS2ST3 Wide Fix: 0.778 LS2ST1
Wide Zoom: 1.1 ~ 1.3 LS2SD2 Standard: 1.54 ~ 1.93 LS2LT1 Semi Long: 1.93 ~
2.9 LS2LT2 Long Zoom: 3 ~ 5 LS2ST2 Short Throw: 0.77~1.1 LS2ST4 Semi Throw:
1.25~1.6 Zoom Ratio LS2ST3 Wide Fix: Fixed LS2ST1 Wide Zoom: 1.18x LS2ST2
Short Throw: 1.42x LS2ST4 Semi Throw: 1.28x LS2SD2 Standard: 1.25x LS2LT1
Semi Long: 1.5x LS2LT2 Long Zoom: 1.67x Lens Shift Vertical: -15% ~ 55%
Horizontal: -5%~5%, Standard Lens Keystone Correction Vertical: ± 30 degrees
Horizontal: ± 30 degrees Projection Size 50" ~ 500" , Standard Lens Projection
Offset N/A Display Projection System DLP Single 0.67" WUXGA DMD type DC3 DMD
Chip Brightness 7000 ANSI Lumens Contrast Ratio* 3,000,000:1 Display Color 1.07
Billion Colors Aspect Ratio Native 16:10 (6 aspect ratio selectable) Light Source
Laser diodes Light Source Life* 20,000/38,000/70,000 hours(Normal/Eco/Dimming)
Native Resolution 1920x1200 pixels Audio Built-in Speaker 20W (10Wx2) Feature
Security Security Bar,Kensington anti-theft lock slot Feature Rec.709 96% Blank to
True Black 4K Compatible DICOM Simulation Mode, 360 Degree and Portrait
Projection,Corner fit Custom Lightsource Mode (light power adjustment) Dust Proof
Engine 24/7 Hours Operating Blanking Dynamic Dimming Compatibility Resolution
Support VGA (640 x 480) to WUXGA (1920 x 1200) Horizontal Frequency 15~102
KHz Vertical Scan Rate 23 ~ 120 Hz HDTV Compatibility 480i, 480p, 576i, 576p,
720p, 1080i, 1080p Video Compatibility NTSC, PAL, SECAM Power Power
Consumption (Max/Normal/Eco) 650W/600W/400W Standby Power Consumption
Normal & 0.5Watts. Network & 2W. Dimension and Weight Product Dimensions
(WxHxD) 525x216 x470 mm (with feet) Product Weight 24 kg (without lens)
Operation Condition Operating Temperature 0 ~ 40 °C Noise Level (Normal/Eco)
36/34dBA Accessories Accessories (Standard) Installation Guide Safety Guide
Remote Control AA Battery x2 VGA cable(1.8m) Power Cord 3pin VESA to BNC
Cable Warranty card (by Region) Accessories (Optional) Instashow WDC10 Ceiling
Mount (CMG6) LS2ST3 Wide Fix (5J.JDH37.002) LS2ST1 Wide Zoom (5J.JDH37.011)
LS2ST2 Short Throw(5A.JK337.001) LS2ST4 Semi Throw(5A.JK337.011) LS2SD2
Standard (5J.JEN37.001) LS2LT1 Semi Long (5J.JDH37.032) LS2LT2 Long Zoom
(5J.JDH37.041) OSD On Screen Display Language Arabic/Bulgarian/ Croatian/
Czech/ Danish/ Dutch/ English/ Finnish/ French/ German/ Greek/ Hindi/ Hungarian/
Italian/ Indonesian/ Japanese/ Korean/ Norwegian/ Polish/ Portuguese/ Romanian/
Russian/ Simplified Chinese/Spanish/ Swedish/ Turkish/ Thai/ Traditional Chinese

(28 Languages) InstaShow Host Power Supply 100 ~ 240V AC