

DELL PowerEdge R550/ 8x 3,5"/ 2x Xeon 4314/ 64GB/ 2x 480GB SSD/ H755/ 2x 1100W/ iDRAC 9 Ent.15G./ 2U/ 3Y PS on-site

cena vč DPH: **128247 Kč**

cena bez DPH: 105989 Kč

Kód zboží (ID): 6443517

PN: DLM00357-2

Záruka: 36 měsíců



The Dell EMC PowerEdge R550, with 3rd generation Intel Xeon Scalable processors, offers added flexibility for organizations seeking exceptional value. CPU: 2x Intel Xeon Silver 4314 2.4G, 16C/32T, 10.4GT/s, 24M Cache, Turbo, HT (135W)
DDR4-2666 RAM: 2x 32GB 3200MT/s, Dual Rank, 16Gb BASE x8, (max 8x RAM per CPU) HDD:2x 480GB SSD SATA Read Intensive 6Gbps 2.5in Hot-plug AG Drive, 3.5in HYB CARR, max 8x 3,5'' HDD Řadič RAID: H755, raid 0, 1, 5, 6, cache 8GB Optická mechanika : Ne LAN: 2x 1Gb LOM + Broadcom 57412 Dual Port 10GbE SFP+, OCP NIC 3.0 Šasi : Rack 2U Správa : iDRAC9 Enterprise 15G Napájení: Dual, Hot-plug, Fully Redundant Power Supply (1+1), 1100W Titanium, max. 2x PSU ReadyRails Sliding Rails Without Cable Management Arm Riser 1 CPU, 1x16 LP+ 1x8(x4 link) LP PowerEdge 2U Standard Bezel Záruka: 3y Prosupport NBD onsite 2 CPU, 3x16 LP+ 1x8(x4 link) LP Front Ports • 1 x Dedicated iDRAC (Micro-AB USB) port • 1 x USB 2.0 • 1 x VGA Rear Ports • 1 x USB 2.0 • 1 x Serial (optional) • 1 x USB 3.0 • 1 x VGA • 1 x iDRAC dedicated port • Height - 86.8 mm (3.41 inches) • Width - 482 mm (18.97 inches) • Depth - 721.69 mm (28.72 inches) with bezel, 685.78 mm (27.00 inches) without bezel

The Dell EMC PowerEdge R550, with 3rd generation Intel Xeon Scalable processors, offers added flexibility for organizations seeking exceptional value. CPU: 2x Intel Xeon Silver 4314 2.4G, 16C/32T, 10.4GT/s, 24M Cache, Turbo, HT (135W)
DDR4-2666 RAM: 2x 32GB 3200MT/s, Dual Rank, 16Gb BASE x8, (max 8x RAM per

CPU) HDD:2x 480GB SSD SATA Read Intensive 6Gbps 2.5in Hot-plug AG Drive, 3.5in HYB CARR, max 8x 3,5'' HDD Řadič RAID: H755, raid 0, 1, 5, 6, cache 8GB Optická mechanika : Ne LAN: 2x 1Gb LOM + Broadcom 57412 Dual Port 10GbE SFP+, OCP NIC 3.0 Šasi : Rack 2U Správa : iDRAC9 Enterprise 15G Napájení: Dual, Hot-plug, Fully Redundant Power Supply (1+1), 1100W Titanium, max. 2x PSU ReadyRails Sliding Rails Without Cable Management Arm Riser 1 CPU, 1x16 LP+ 1x8(x4 link) LP PowerEdge 2U Standard Bezel Záruka: 3y Prosupport NBD onsite 2 CPU, 3x16 LP+ 1x8(x4 link) LP Front Ports • 1 x Dedicated iDRAC (Micro-AB USB) port • 1 x USB 2.0 • 1 x VGA Rear Ports • 1 x USB 2.0 • 1 x Serial (optional) • 1 x USB 3.0 • 1 x VGA • 1 x iDRAC dedicated port • Height – 86.8 mm (3.41 inches) • Width – 482 mm (18.97 inches) • Depth – 721.69 mm (28.72 inches) with bezel, 685.78 mm (27.00 inches) without bezel