

SEASONIC zdroj Prime GX-750 Gold / SSR-750GD2 / aktiv. PFC / 80PLUS Gold

cena vč DPH: **4846 Kč**

cena bez DPH: 4005 Kč

Kód zboží (ID): 6478778

PN: PRIME-GX-750

Záruka: 120 měsíců



80PLUS® Gold Cybenetics Efficiency Level TBA Cybenetics Noise Level TBA Form Factor Intel ATX 12 V Dimensions 140 mm (W) x 150 mm (L) x 86 mm (H) Fan Information Fan Size 135 mm Fan Control Premium Hybrid Fan Control Fan Bearing Fluid Dynamic Bearing Life Expectancy 50,000 hours at 40 °C, 15 % - 65 % RH Cable Information Modularity Fully Modular Cable type Flat black cables Electrical Features Operating Temperature 0 - 50 °C (derating from 100 % to 80 % from 40 °C to 50 °C) MTBF @ 25 °C, excl. fan 150,000 hours AC Input Full Range Protection OPP, OVP, UVP, OCP, OTP, SCP Safety and Environmental Safety and EMC cTUVus, TUV, CB, CCC, BSMI, EAC, CE Environmental Compliance Energy Star, RoHS, WEEE, ErP Lot 6, REACH Warranty 12 Years Power Output AC Input Voltage: 100 V - 240 V Current: 10 - 5 A Frequency: 50 Hz - 60 Hz DC Output Rail +3.3 V +5 V +12 V -12 V +5 VSB Maximum Power 20 A 20 A 62 A 0.3 A 3 A 100 W 744 W 3.6 W 15 W Total continuous power 750 W

80PLUS® Gold Cybenetics Efficiency Level TBA Cybenetics Noise Level TBA Form Factor Intel ATX 12 V Dimensions 140 mm (W) x 150 mm (L) x 86 mm (H) Fan Information Fan Size 135 mm Fan Control Premium Hybrid Fan Control Fan Bearing Fluid Dynamic Bearing Life Expectancy 50,000 hours at 40 °C, 15 % - 65 % RH Cable Information Modularity Fully Modular Cable type Flat black cables Electrical Features Operating Temperature 0 - 50 °C (derating from 100 % to 80 % from 40 °C to 50 °C) MTBF @ 25 °C, excl. fan 150,000 hours AC Input Full Range Protection OPP, OVP, UVP, OCP, OTP, SCP Safety and Environmental Safety and EMC cTUVus, TUV, CB, CCC, BSMI, EAC, CE Environmental Compliance Energy Star, RoHS, WEEE,

ErP Lot 6, REACH Warranty 12 Years Power Output AC Input Voltage: 100 V - 240 V
Current: 10 - 5 A Frequency: 50 Hz - 60 Hz DC Output Rail +3.3 V +5 V +12 V -12 V
+5 VSB Maximum Power 20 A 20 A 62 A 0.3 A 3 A 100 W 744 W 3.6 W 15 W Total
continuous power 750 W